

The Fastest Radio Modems

RipEX

Private

Mission-Critical

Mesh

RipEX is a radio modem platform providing a 24/7 reliable service for wireless data transfer in mission-critical applications like SCADA & Telemetry at critical infrastructure such as Power and Water Utilities, Oil & Gas and many others.



Market leader

- 1.7 Mb/s, 256QAM
- Dynamic routing
- Radio and Cellular in one
- Unlimited coverage without Base stations

Performance

- 160, 300, 400, 800, 900 MHz
- 2CPFSK – 256QAM
- 6.25 – 300 kHz channels
- 10 W, Half or Full duplex

Reliability

- Industrial hardened design, -40 to +70 °C
- Each unit tested in climatic chamber
- MTBF > 100 years, Made in Czechia, EU
- Backup routes, 1+1 Redundancy

Security

- IPsec, OpenVPN, AES256
- RADIUS, Firewall, VLAN
- Digitally signed FW, Secure Boot
- HW tamper



Technical parameters

	RipEX2	RipEX2e	RipEX
Max. Speed	1.7 Mb/s @ 256QAM	250 kb/s @ 64QAM	166 kb/s @ 16DEQAM
Speed @ 25 kHz	167 kb/s	125 kb/s	83 kb/s
Channel size	6.25 – 300 kHz	6.25 – 50 kHz	6.25 – 50 kHz
Interfaces	4× ETH, 1× SFP, 1× COM, 1× USB	2× ETH, 2× COM, 1× USB	1× ETH, 2× COM, 1× USB
mPCIe	Yes	No	No
Full-duplex	Yes	No	No

Radio parameters	RipEX2	RipEX2e	RipEX
Frequency bands	135–175; 285–335; 335–400; 400–470; 450–520; 803 – 897; 860 – 960 MHz		135–154; 154–174; 215-240; 300–320; 320–340; 340–360; 368–400; 400–432; 432–470; 470-512; 928–960 MHz
Channel spacing	6.25; 12.5; 25; 50; 100; 150; 200; 250; 300 kHz	6.25; 12.5; 25; 50 kHz	6.25; 12.5; 25; 50 kHz
Frequency stability	±/ 0.5 ppm		±/ 1.0 ppm
Modulations	QAM: 256QAM, 64QAM, 16DEQAM, D8PSK, π/4DQPSK, DPSK FSK: 4CPFSK, 2CPFSK	QAM: 64QAM, 16DEQAM, D8PSK, π/4DQPSK, DPSK FSK: 4CPFSK, 2CPFSK	QAM: 16DEQAM, D8PSK, π/4DQPSK, DPSK FSK: 4CPFSK, 2CPFSK
FEC (Forward Error Correction)	2/3; 3/4; 5/6; Off		3/4; Off
Gross data rate	up to 1.7 Mb/s		up to 167 kb/s
RF Output power	20-40 dBm PEP (0.1-10 W RMS), 1 dB step programmable		20-40 dBm PEP (0.1-10 W RMS), 9 levels programmable
Duty cycle	Continuous		
Rx to Tx Time	< 0.7 ms @ 25 kHz; < 1 ms @ 12.5 kHz channel		< 1.5 ms
Sensitivity	- 97 dBm (256QAM; 12.5 kHz; BER 10-6; 2/3 FEC) -117 dBm (2CPFSK; 12.5 kHz BER 10-6; 3/4 FEC)	- 101 dBm (64QAM; 12.5 kHz; BER 10-6; 2/3 FEC) -117 dBm (2CPFSK; 12.5 kHz BER 10-6; 3/4 FEC)	- 99 dBm (16DEQAM; 12.5 kHz; BER 10-6; 3/4 FEC) -111 dBm (2CPFSK; 12.5 kHz BER 10-6; 3/4 FEC)
Electrical			
Primary power	10 to 30 VDC, negative GND		
Rx	8.3 W @ 24 V		4.8 W @ 24 V
Tx	12 – 40 W @ 24 V		13 – 38 W @ 24 V
Sleep mode	0.01 W		0.1 W
Interfaces			
Ethernet	4x 10/100/1000 Base-T Auto MDI/MDIX	4x RJ45	2x 10/100/1000 Base-T Auto MDI/MDIX 2x RJ45
SFP	1x 10/100/1000 Base or T/1000Base-SX or 1000Base-LX	1x SFP	No
Serial	1x RS232/RS485 SW configurable 2x RS232 (mPCIe expansion board) 600 b/s – 2 Mb/s	1x DB9F 1x RJ45	1x RS232/RS485 SW configurable 1x DB9F 1x RS232 600 b/s – 1 Mb/s
USB	USB 3.0 / Host A		USB 1.1 / Host A
Antenna	2x TNC female @ 50 ohms SW configurable: 1x Rx/Tx or 1x Rx + 1x Tx		1x TNC female @ 50 ohms, Rx/Tx
Inputs/Outputs	1x HW alarm input, 1x HW alarm output, 1x Sleep input, 2x DI, 2x DO, 1x DiffDI (when mPCIe-COMs is not used)		1x HW alarm input, 1x HW alarm output, 1x Sleep input
Optional Expansions	1x mPCIe: Cellular module or 2x RS232 or GPS		No
Indication LEDs			GPS
LED panel	5x tri-color status LEDs (SYS, AUX, Rx, Tx, COM)		7x tri-color status LEDs (Power, ETH, COM1, COM2, Rx, Tx, Status)
ETH	4x RJ45 (Link and Activity LEDs), 1x SFP (Status LED)		2x RJ45 (Link and Activity LEDs)
Environmental			
IP Code (Ingress Protection)	IP41, IP42, IP52		IP40, IP51
MTBF (Mean Time Between Failure)	> 900 000 hours (> 100 years)		
Operating temperature	- 40 to +70 °C (- 40 to +158 °F)		
Operating humidity	5 to 95% non-condensing		
Mechanical			
Casing	Rugged die-cast aluminium		
Dimensions	60 H x 185 W x 125 D mm (2.34 x 7.2 x 4.9 in)		50 H x 150 W x 118 D mm (1.97 x 5.9 x 4.65 in)
Weight	1.55 kg (3.4 lbs)		1.1 kg (2.4 lbs)
Mounting	DIN rail, L-bracket, Flat-bracket, 19" Rack chassis		
Radio channel			
Radio protocols	Transparent @ Bridge; Flexible, Base driven @ Router		
Routing (Radio channel included)	Static, Dynamic		Static, Backup routes
Multi master applications	Yes		
Report by exception	Yes		
Collision Avoidance Capability	Yes		
Remote to Remote communication	Yes		
Repeaters	Store-and-forward; Every unit; Unlimited number		
QoS	8 levels on all interfaces, Radio included		
SCADA protocols			
Serial	DNP3, DF1, IEC101, Modbus RTU, PR2000, RDS, Siemens 3964(R), COMLI, SAIA S-bus, Mars-A, UNI, Async Link...		
Ethernet	Modbus TCP, IEC104, DNP3 TCP, Comii TCP...		
Serial to IP converters	Modbus RTU / Modbus TCP, DNP3 / DNP3 TCP, Terminal server		
Security			
Management	HTTPS (Web), SSH (CL)		
Role-based access control (RBAC)	4 levels (Guest, Tech, SecTech, Admin)		2 levels (Guest, Admin)
Encryption	AES256 - CCM		
VPN	IPsec, OpenVPN, GRE		
VLAN	IEEE 802.1Q (tagging), Q-in-Q for Transparent mode		
AAA protocol	RADIUS		No
Firewall	Layer 2 - MAC, Layer 3 - IP, Layer 4 - TCP/UDP		
FW	Digitally signed, Secure boot		
HW tamper	Case opening evidence		No
Diagnostics			
Radio link testing	Ping with RSS, MSE (DQ)		
Logs	Status, Event log		Status
Statistics	Historical and differential statistics (Rx/Tx packets etc.) for all interfaces, for Radio channel in addition RSS, MSE (DQ), Repeats etc.		
Monitoring	Real time analysis of all interfaces (Radio, ETH 1-5 , COM 1-3, Cellular...)		
NTP	Client, Server		
SNMP	SNMPv1, SNMPv2c, SNMPv3, SNMP Trap / Inform alarms generation as per settings		
SMS	SMS alarms generation as per settings		No
Approvals	CE (RED), FCC, ... Ask for others		No

Technical parameters are subject to change without prior notification. For more details see [User manuals](#).

