



DELL EMC NETWORKING S5148F-ON SERIES SWITCH

Programmable high-performance open networking top-of-rack switch with native 25G server ports and 100G network fabric connectivity

The Dell EMC S5148 switch is an innovative, future-ready Top-of-Rack (ToR) open networking switch providing excellent capabilities and cost-effectiveness for the enterprise, mid-market, Tier2 cloud and NFV service providers with demanding compute and storage traffic environments.

The S5148F-ON 25GbE switch is Dell EMC's latest disaggregated hardware and software data center networking solution that provides state-of-the-art data plane programmability, backward compatible 25GbE server port connections, 100GbE uplinks, storage optimized architecture, and a broad range of functionality to meet the growing demands of today's data center environment now and in the future.

The compact S5148F-ON model design provides industry-leading density with up to 72 ports of 25GbE or up to 48 ports of 25GbE and 6 ports of 100GbE in a 1RU form factor.

Using industry-leading hardware and a choice of Dell EMC's OS10 or select 3rd party network operating systems and tools, the S5148F-ON Series offers flexibility by provision of configuration profiles and delivers non-blocking performance for workloads sensitive to packet loss. The compact S5148F-ON model provides multi rate speed enabling denser footprints and simplifying migration to 25GbE server connections and 100GbE fabrics.

Data plane programmability allows the S5148F-ON to meet the demands of the converged software defined data center by offering support for any future or emerging protocols, including hardware-based VXLAN (Layer 2 and Layer 3 gateway) support. Priority-based flow control (PFC), data center bridge exchange (DCBX) and enhanced transmission selection (ETS) make the S5148F-ON an excellent choice for DCB environments.

The Dell EMC S5148F-ON model supports the open source Open Network Install Environment (ONIE) for zero touch installation of alternate network operating systems.

Maximum performance and functionality

The Dell EMC Networking S-Series S5148F-ON is a high-performance, multi-function, 10/25/40/50/100 GbE ToR switch purpose-built for applications in high-performance data center, cloud and computing environments.

In addition, the S5148F-ON incorporates multiple architectural features that optimize data center network flexibility, efficiency, and availability, including IO panel to PSU airflow or PSU to IO panel airflow for hot/cold aisle environments, and redundant, hot-swappable power supplies and fans.

Key applications

- Organizations looking to enter the software-defined data center era with a choice of networking technologies designed to deliver the flexibility they need
- Use cases that require customization to any packet processing steps or supporting new protocols
- Native high-density 25 GbE ToR server access in high-performance data center environments
- 25 GbE backward compatible to 10G and 1G for future proofing and data center server migration to faster uplink speeds.
- Capability to support mixed 25G and 10G servers on front panel ports without any limitations
- iSCSI storage deployment including DCB converged lossless transactions
- Suitable as a ToR or Leaf switch in 100G Active Fabric implementations
- As a high speed VXLAN L2/L3 gateway that connects the hypervisor-based overlay networks with non-virtualized infrastructure
- Emerging applications requiring hardware support for new protocols

Key features

- 1RU high-density 25/10/1 GbE ToR switch with up to forty eight ports of native 25 GbE (SFP28) ports supporting 25 GbE without breakout cables
- Multi-rate 100GbE ports support 10/25/40/50 GbE
- 3.6 Tbps (full-duplex) non-blocking, cut-through switching fabric delivers line-rate performance under full load**
- Programmable packet modification and forwarding
- Programmable packet mirroring and multi-pathing
- Converged network support for DCB and ECN capability
- IO panel to PSU airflow or PSU to IO panel airflow
- Redundant, hot-swappable power supplies and fans
- IEEE 1588v2 PTP hardware support
- Supports the open source Open Network Install Environment (ONIE) for zero touch installation of alternate network operating systems

- Fibre Channel, FCoE, FCoE transit (FIP Snooping) and NPIV Proxy Gateway (NPG), Fibre Channel Forwarding (FCF)
- Full data center bridging (DCB) support for lossless iSCSI SANs, RoCE and converged network.
- Redundant, hot-swappable power supplies and fans
- I/O panel to PSU airflow or PSU to I/O panel airflow (reversible airflow)
- VRF-lite enables sharing of networking infrastructure and provides L3 traffic isolation across tenants
- 16, 28, 40, 52, 64 10GbE ports available
- OS10 Premium Edition software enables Dell EMC layer 2 and 3 switching and routing protocols with integrated IP Services, Quality of Service, Manageability and Automation features
- Platform agnostic via standard hardware abstraction layer (OCP-SAI)
- Unmodified Linux kernel and unmodified Linux distribution
- OS10 Open Edition software decoupled from L2/L3 protocol stack and services
- Leverage common open source tools and best-practices (data models, commit rollbacks)
- Increase VM Mobility region by stretching L2 VLAN within or across two DCs with unique VLT capabilities

Key features with Dell EMC Networking OS10

- Consistent DevOps framework across compute, storage and networking elements
- Standard networking features, interfaces and scripting functions for legacy network operations integration
- Standards-based switching hardware abstraction via Switch Abstraction Interface (SAI)
- Pervasive, unrestricted developer environment via Control Plane Services (CPS)
- Open and programmatic management interface via Common Management Services (CMS)
- Scalable L2 and L3 Ethernet Switching with GoS, ACL and a full complement of standards based IPv4 and IPv6 features including OSPF, BGP and PBR
- Enhanced mirroring capabilities including local mirroring, Remote Port Mirroring (RPM), and Encapsulated Remote Port Mirroring (ERPM).
- Converged network support for DCB, with priority flow control (802.1Qbb), ETS (802.1Qaz), DCBx and iSCSI TLV
- Rogue NIC control provides hardware-based protection from NICS sending out excessive pause frames

Product	Description
S5148F-ON	S5148F, 48x 25GbE SFP+, 6x 100GbE QSFP28, 2x AC PSU, 4x Fans, I/O Panel to PSU Airflow S5148F, 48x 25GbE SFP+, 6x 100GbE QSFP28, 2x AC PSU, 4x Fans, PSU to I/O Panel Airflow S5148F, 48x 25GbE SFP+, 6x 100GbE QSFP28, 2x AC PSU, 4x Fans, I/O Panel to PSU Airflow - TAA S5148F, 48x 25GbE SFP+, 6x 100GbE QSFP28, 2x AC PSU, 4x Fans, PSU to I/O Panel Airflow - TAA S5148F, 48x 25GbE SFP+, 6x 100GbE QSFP28, 2x DC PSU, 4x Fans, PSU to I/O Panel Airflow – NEBS Level 3 Certified*
Redundant power supplies	S5100, AC Power Supply, IO Panel to PSU Airflow S5100, AC Power Supply, PSU to IO Panel Airflow S5100, DC Power Supply, PSU to IO Panel Airflow*
Fans	S5100 fan module, IO Panel to PSU Airflow S5100 fan module, PSU to IO Panel Airflow
Optics	Transceiver, 100GbE, SR4 QSFP28 Transceiver, 100GbE, LR4 QSFP28 Transceiver, 100GbE, LR4Lite QSFP28 Transceiver, 100GbE, PSM4 10Km QSFP28 (*) Transceiver, 100GbE, CWDM4 2Km QSFP28 (*) Transceiver, 100GbE, PSM4 500m QSFP28 (*) Transceiver, 40GbE, SR4 optic QSFP+ Transceiver, 40GbE, eSR4 optic QSFP+ Transceiver, 40GbE, LR4 optic QSFP+ Transceiver, 40GbE, ER4 optics QSFP+ Transceiver, 40GbE, PSM4 10Km, QSFP+ Transceiver, 40GbE, PSM4-LR MPO 10Km QSFP+ to LC Transceiver, 40GbE, LM4 / SM4 Duplex QSFP+ Transceiver, 25GbE, SR4 SFP28 Transceiver, 25GbE, LR4 SFP28 Transceiver, 10GbE, SR4 SFP+ Transceiver, 10GbE, LR4 SFP+ Transceiver, 1GbE, SR4 SFP+ Transceiver, 1GbE, LR4 SFP+

Product	Description
Cables	100GbE, 4x25GbE, QSFP28 to 4xSFP28, passive DAC
	100GbE, QSFP28 to QSFP28, active optical
	100GbE, QSFP28 to QSFP28, passive DAC
	100GbE, 2x50GbE, QSFP28 to 2xQSFP28, passive DAC, breakout (*)
	40GbE, QSFP+ to QSFP+, active optical
	40GbE, QSFP+ to QSFP+, passive DAC
	40GbE, MTP to 4xLC optical breakout
	40GbE, 4x10GbE, QSFP+ to 4xSFP+, passive DAC
	25GbE SFP28 to SFP28, passive DAC, 1M, 2M, 3M, 5M
	25GbE SFP28 to SFP28, active optical cable, 7M, 10M, 15M, 20M

Technical specifications

Physical	802.3ab Gigabit Ethernet (1000Base-T)	General IPv4 Protocols
48 line-rate 25 Gigabit Ethernet SFP28 ports	802.3ad Link Aggregation with LACP	791 IPv4
6 line-rate 100 Gigabit Ethernet QSFP28 ports	802.3ae 10 Gigabit Ethernet (10GBase-X)	792 ICMP
1 RJ45 console/management port with RS232 signaling	802.3ba 40 Gigabit Ethernet (40GBase-X)	826 ARP
1 Micro-USB type B optional console port	802.3i Ethernet (10Base-T)	1027 Proxy ARP
1 10/100/1000 Base-T Ethernet port used as management port	802.3u Fast Ethernet (100Base-TX)	1035 DNS (client)
1 USB type A port for the external mass storage	802.3z Gigabit Ethernet (1000BaseX)	1042 Ethernet Transmission
Size: 1 RU, 1.72 h x 17.1 w x 18.1" d (4.4 h x 43.4 w x 46 cm d)	802.1D Bridging, STP	1191 Path MTU Discovery
Weight: 22lbs (9.97kg)	802.1p L2 Prioritization	1305 NTPv4
ISO 7779 A-weighted sound pressure level: 59.6 dBA at 73.4°F (23°C)	802.1Q VLAN Tagging, Double VLAN Tagging, GVRP	1519 CIDR
Power supply: 100–240 VAC 50/60 Hz	802.1Qbb PFC	1812 Routers
Max. thermal output: 1956 BTU/h	802.1Qaz ETS	1858 IP Fragment Filtering
Max. current draw per system:	802.1s MSTP	2131 DHCP (server and relay)
5.73A/4.8A at 100/120V AC	802.1w RSTP	5798 VRRP
2.87A/2.4A at 200/240V AC	802.1X Network Access Control	3021 31-bit Prefixes
Max. power consumption: 516 Watts (AC)	802.3ab Gigabit Ethernet (1000BASE-T) or breakout	3046 DHCP Option 82 (Relay)
Typ. power consumption: 421 Watts (AC) with all optics loaded	802.3ac Frame Extensions for VLAN Tagging	1812 Requirements for IPv4 Routers
Max. operating specifications:	802.3ad Link Aggregation with LACP	1918 Address Allocation for Private Internets
Operating temperature: 32° to 113°F (0° to 45°C)	802.3ae 10 Gigabit Ethernet (10GBase-X)	2474 Diffserv Field in IPv4 and Ipv6 Headers
Operating humidity: 5 to 90% (RH), non-condensing	802.3ba 40 Gigabit Ethernet (40GBase-SR4, 40GBase-CR4, 40GBase-LR4, 100GBase-SR10, 100GBase-LR4, 100GBase-ER4) on optical ports	2596 Assured Forwarding PHB Group
Fresh Air Compliant to 45C	802.3bj 100 Gigabit Ethernet	3195 Reliable Delivery for Syslog
Max. non-operating specifications:	802.3u Fast Ethernet (100Base-TX) on mgmt ports	3246 Expedited Assured Forwarding
Storage temperature: -40° to 158°F (-40° to 70°C)	802.3x Flow Control	4364 VRF-lite (IPv4 VRF with OSPF and BGP)*
Storage humidity: 5 to 95% (RH), non-condensing	802.3z Gigabit Ethernet (1000Base-X) with QSA	
	ANSI/TIA-1057 LLDP-MED	General IPv6 Protocols
	Jumbo MTU support 9,416 bytes	1981 Path MTU Discovery*
Redundancy		2460 IPv6
Hot swappable redundant power supplies	Layer2 Protocols	2461 Neighbor Discovery*
Hot swappable redundant fans	4301 Security Architecture for IPsec*	2462 Stateless Address AutoConfig
	4302 IPsec Authentication Header*	2463 ICMPv6
	4303 ESP Protocol*	2464 Ethernet Transmission
Performance	802.1D Compatible	2675 Jumbo grams
Switch fabric capacity: 3.6Tbps	802.1p L2 Prioritization	3587 Global Unicast Address Format
Packet buffer memory: 16MB	802.1Q VLAN Tagging	4291 IPv6 Addressing
CPU memory: 16GB	802.1s MSTP	2464 Transmission of IPv6 Packets over Ethernet Networks
MAC addresses: Up to 512K	802.1w RSTP	2711 IPv6 Router Alert Option
ARP table: Up to 256K	802.1t RPVST+	4007 IPv6 Scoped Address Architecture
IPv4 routes: Up to 128K	802.3ad Link Aggregation with LACP	4213 Basic Transition Mechanisms for IPv6 Hosts and Routers
IPv6 routes: Up to 64K	802.3ad Link Aggregation with LACP	4291 IPv6 Addressing Architecture
Multicast hosts: Up to 64K	VLT Virtual Link Trunking	5095 Deprecation of Type 0 Routing Headers in IPv6
Link aggregation: Unlimited links per group, up to 36 groups		IPv6 Management support (telnet, FTP, TACACS, RADIUS, SSH, NTP)
Layer 2 VLANs: 4K		
MSTP: 64 instances	RFC Compliance	
LAG Load Balancing: User Configurable (MAC, IP, TCP/UDPport)	768 UDP	OSPF (v2/v3)
	793 TCP	1587 NSSA
	854 Telnet	1745 OSPF/BGP interaction
	959 FTP	1765 OSPF Database overflow
	1321 MD5	2154 MD5
	1350 TFTP	2328 OSPFv2
	2474 Differentiated Services	2370 Opaque LSA
	2698 Two Rate Three Color Marker	3101 OSPF NSSA
	3164 Syslog	3623 OSPF Graceful Restart (Helper mode)*
	4254 SSHv2	
IEEE Compliance		
802.1AB LLDP		
TIA-1057 LLDP-MED		
802.1s MSTP		
802.1w RSTP		

BGP

1997	Communities
2385	MD5
2439	Route Flap Damping
2796	Route Reflection
2842	Capabilities
2918	Route Refresh
3065	Confederations
4271	BGP-4
4360	Extended Communities
4893	4-byte ASN
5396	4-byte ASN Representation
5492	Capabilities Advertisement

Linux Distribution

Debian Linux version 8.4
Linux Kernel 3.16

MIBS

IP MIB– Net SNMP
IP Forward MIB– Net SNMP
Host Resources MIB– Net SNMP
IF MIB – Net SNMP
LLDP MIB
Entity MIB
LAG MIB
Dell-Vendor MIB
TCP MIB – Net SNMP
UDP MIB – Net SNMP
SNMPv2 MIB – Net SNMP

Network Management

SNMPv1/2
SSHv2
FTP, TFTP, SCP
Syslog
Port Mirroring
RADIUS
802.1X
Support Assist (Phone Home)
Netconf APIs
XML Schema
CLI Commit (Scratchpad)

Automation

Control Plane Services APIs
Linux Utilities and Scripting Tools

Quality of Service

Access Control Lists
Prefix List
Route-Map
Rate Shaping (Egress)
Rate Policing (Ingress)
Scheduling Algorithms
 Round Robin
 Weighted Round Robin
 Deficit Round Robin
 Strict Priority
Weighted Random Early Detect

Security

2865 RADIUS
3162 Radius and IPv6
4250, 4251, 4252, 4253, 4254 SSHv2

*Future release

**Packet sizes over 147 Bytes

Data center bridging

802.1Qbb Priority-Based Flow Control
802.1Qaz Enhanced Transmission Selection (ETS)*
Data Center Bridging eXchange (DCBx)
DCBx Application TLV (iSCSI, FCoE*)

Regulatory compliance

Safety

UL/CSA 60950-1, Second Edition
EN 60950-1, Second Edition
IEC 60950-1, Second Edition Including All National Deviations and Group Differences
EN 60825-1 Safety of Laser Products Part 1: Equipment
Classification Requirements and User's Guide
EN 60825-2 Safety of Laser Products Part 2: Safety of Optical Fibre Communication Systems
FDA Regulation 21 CFR 1040.10 and 1040.11

Emissions & Immunity

EMC compliance
FCC Part 15 (CFR 47) (USA) Class A
ICES-003 (Canada) Class A
EN55032: 2015 (Europe) Class A
CISPR32 (International) Class A
AS/NZS CISPR32 (Australia and New Zealand) Class A
VCCI (Japan) Class A
KN32 (Korea) Class A
CNS13438 (Taiwan) Class A
CISPR22
EN55022
EN61000-3-2
EN61000-3-3
EN61000-6-1
EN300 386
EN 61000-4-2 ESD
EN 61000-4-3 Radiated Immunity
EN 61000-4-4 EFT
EN 61000-4-5 Surge
EN 61000-4-6 Low Frequency Conducted Immunity

NEBS

GR-63-Core
GR-1089-Core
ATT-TP-76200
VZ.TPR.9305

RoHS

RoHS 6 and China RoHS compliant

Certifications

Japan: VCCI V3/2009 Class A
USA: FCC CFR 47 Part 15, Subpart B:2009, Class A

Warranty

1 Year Return to Depot

IT Lifecycle Services for Networking

Experts, insights and ease

Our highly trained experts, with innovative tools and proven processes, help you transform your IT investments into strategic advantages.



Plan & Design

Let us analyze your multivendor environment and deliver a comprehensive report and action plan to build upon the existing network and improve performance.



Deploy & Integrate

Get new wired or wireless network technology installed and configured with ProDeploy. Reduce costs, save time, and get up and running fast.



Educate

Ensure your staff builds the right skills for long-term success. Get certified on Dell EMC Networking technology and learn how to increase performance and optimize infrastructure.



Manage & Support

Gain access to technical experts and quickly resolve multivendor networking challenges with ProSupport. Spend less time resolving network issues and more time innovating.



Optimize

Maximize performance for dynamic IT environments with Dell EMC Optimize. Benefit from in-depth predictive analysis, remote monitoring and a dedicated systems analyst for your network.



Retire

We can help you resell or retire excess hardware while meeting local regulatory guidelines and acting in an environmentally responsible way.

Learn more at
Dell.com/LifecycleServices

Learn more at Dell.com/Networking