

S5720-EI Series Enhanced Gigabit Switches

Huawei S5720-EI series switches provide flexible all-gigabit access and enhanced 10GE uplink port scalability. They are widely used as access/aggregation switches in enterprise campus networks or gigabit access switches in data centers.

Introduction




The S5720-EI series enhanced Gigabit Ethernet switches are switches that provide flexible GE access ports (including optical, electrical, and combo ports) and 10GE uplink ports. Built on next-generation high-performance processors and Huawei Versatile Routing Platform (VRP), the S5720-EI provides larger table sizes and higher hardware processing capabilities than equivalent switches. Besides, it provides comprehensive service processing capabilities, enhanced security control, and mature IPv6 features, and supports MACsec, intelligent stack (iStack), flexible Ethernet networking, and easy operations and maintenance (O&M). With all these advantages, the S5720-EI is widely used for access/aggregation in enterprise campus networks or gigabit access in data center networks.








Product Overview









Models and Appearances






The following models are available in the S5720-EI series.

Models and appearances of the S5720-EI series

Appearance	Description
 S5720-32P-EI-AC	<ul style="list-style-type: none"> • 24 10/100/1000 Ethernet ports, 4 100/1000 SFP ports, 4GE SFP ports, 2 QSFP+ dedicated stack ports • AC power supply, supporting Redundant Power Supply (RPS), power socket on the front panel • Forwarding performance: 48 Mpps • Switching capacity: 598 Gbit/s
 S5720-32X-EI-AC	<ul style="list-style-type: none"> • 24 10/100/1000 Ethernet ports, 4 100/1000 SFP ports, 4 10GE SFP+ ports, 2 QSFP+ dedicated stack ports • AC power supply, supporting RPS, power socket on the front panel • Forwarding performance: 102 Mpps • Switching capacity: 598 Gbit/s
 S5720-32X-EI-24S-AC	<ul style="list-style-type: none"> • 24 Gig SFP ports, 4 10/100/1000 Ethernet ports, 4 10GE SFP+ ports, 2 QSFP+ dedicated stack ports • AC power supply, supporting RPS, power socket on the front panel • Forwarding performance: 102 Mpps

Appearance	Description
 <p>S5720-32X-EI-24S-DC</p>	<ul style="list-style-type: none"> Switching capacity: 598 Gbit/s 24 Gig SFP ports, 4 10/100/1000 Ethernet ports, 4 10GE SFP+ ports, 2 QSFP+ dedicated stack ports DC power supply, supporting RPS, power socket on the front panel Forwarding performance: 102 Mpps Switching capacity: 598 Gbit/s
 <p>S5720-36C-EI-28S-AC</p>	<ul style="list-style-type: none"> 28 Gig SFP ports (4 of which are dual-purpose 10/100/1000 ports), 4 10GE SFP+ ports One extended slot Double hot swappable AC or DC power supplies, one AC power supply equipped by default Forwarding performance: 132 Mpps Switching capacity: 598 Gbit/s
 <p>S5720-36C-EI-28S-DC</p>	<ul style="list-style-type: none"> 28 Gig SFP ports (4 of which are dual-purpose 10/100/1000 ports), 4 10GE SFP+ ports One extended slot Double hot swappable AC or DC power supplies, one DC power supply equipped by default Forwarding performance: 132 Mpps Switching capacity: 598 Gbit/s
 <p>S5720-36C-EI-AC</p>	<ul style="list-style-type: none"> 28 10/100/1000 Ethernet ports (4 of which are dual-purpose 10/100/1000 or SFP ports), 4 10GE SFP+ ports One extended slot Double hot swappable AC or DC power supplies, one AC power supply equipped by default Forwarding performance: 132 Mpps Switching capacity: 598 Gbit/s
 <p>S5720-36C-PWR-EI-AC</p>	<ul style="list-style-type: none"> 28 10/100/1000 Ethernet PoE+ ports (4 of which are dual-purpose 10/100/1000 or SFP ports), 4 10GE SFP+ ports One extended slot PoE+ Double hot swappable AC or DC power supplies, one AC power supply equipped by default Forwarding performance: 132 Mpps Switching capacity: 598 Gbit/s
 <p>S5720-36PC-EI-AC</p>	<ul style="list-style-type: none"> 28 10/100/1000 Ethernet ports (4 of which are dual-purpose 10/100/1000 or SFP ports), 4 GE SFP ports One extended slot Double hot swappable AC or DC power supplies, one AC power supply equipped by default Forwarding performance: 78 Mpps Switching capacity: 598 Gbit/s
 <p>S5720-50X-EI-AC</p>	<ul style="list-style-type: none"> 46 10/100/1000 Ethernet ports, 4 10GE SFP+ ports, 2 QSFP+ dedicated stack ports AC power supply, supporting RPS, power socket on the front panel

Appearance	Description
	<ul style="list-style-type: none"> Forwarding performance: 129 Mpps Switching capacity: 598 Gbit/s
 <p>S5720-50X-EI-DC</p>	<ul style="list-style-type: none"> 46 10/100/1000 Ethernet ports, 4 10GE SFP+ ports, 2 QSFP+ dedicated stack ports DC power supply, supporting RPS, power socket on the front panel Forwarding performance: 129 Mpps Switching capacity: 598 Gbit/s
 <p>S5720-50X-EI-46S-AC</p>	<ul style="list-style-type: none"> 46 Gig SFP ports, 4 10GE SFP+ ports, 2 QSFP+ dedicated stack ports AC power supply, supporting RPS, power socket on the front panel Forwarding performance: 129 Mpps Switching capacity: 598 Gbit/s
 <p>S5720-50X-EI-46S-DC</p>	<ul style="list-style-type: none"> 46 Gig SFP ports, 4 10GE SFP+ ports, 2 QSFP+ dedicated stack ports DC power supply, supporting RPS, power socket on the front panel Forwarding performance: 129 Mpps Switching capacity: 598 Gbit/s
 <p>S5720-52X-EI-AC</p>	<ul style="list-style-type: none"> 48 10/100/1000 Ethernet ports, 4 10GE SFP+ ports, 2 QSFP+ dedicated stack ports AC power supply, supporting RPS Forwarding performance: 132 Mpps Switching capacity: 598 Gbit/s
 <p>S5720-52P-EI-AC</p>	<ul style="list-style-type: none"> 48 10/100/1000 Ethernet ports, 4 GE SFP ports, 2 QSFP+ dedicated stack ports AC power supply, supporting RPS Forwarding performance: 78 Mpps Switching capacity: 598 Gbit/s
 <p>S5720-56C-EI-48S-AC</p>	<ul style="list-style-type: none"> 48 Gig SFP ports, 4 10GE SFP+ ports One extended slot Double hot swappable AC or DC power supplies, one AC power supply equipped by default Forwarding performance: 162 Mpps Switching capacity: 598 Gbit/s
 <p>S5720-56C-EI-48S-DC</p>	<ul style="list-style-type: none"> 48 Gig SFP ports, 4 10GE SFP+ ports One extended slot Double hot swappable AC or DC power supplies, one DC power supply equipped by default Forwarding performance: 162 Mpps Switching capacity: 598 Gbit/s
 <p>S5720-56C-EI-AC</p>	<ul style="list-style-type: none"> 48 10/100/1000 Ethernet ports, 4 10GE SFP+ ports One extended slot Double hot swappable AC or DC power supplies, one AC power supply equipped by default Forwarding performance: 162 Mpps Switching capacity: 598 Gbit/s

Appearance	Description
 <p>S5720-56C-EI-DC</p>	<ul style="list-style-type: none"> • 48 10/100/1000 Ethernet ports, 4 10GE SFP+ ports • One extended slot • Double hot swappable AC or DC power supplies, one DC power supply equipped by default • Forwarding performance: 162 Mpps • Switching capacity: 598 Gbit/s
 <p>S5720-56C-PWR-EI-AC</p>	<ul style="list-style-type: none"> • 48 10/100/1000 Ethernet PoE+ ports, 4 10GE SFP+ ports • One extended slot • PoE+ • Double hot swappable AC or DC power supplies, one AC power supply equipped by default • Forwarding performance: 162 Mpps • Switching capacity: 598 Gbit/s
 <p>S5720-56C-PWR-EI-AC1</p>	<ul style="list-style-type: none"> • 48 10/100/1000 Ethernet PoE+ ports, 4 10GE SFP+ ports • One extended slot • PoE+ • Double hot swappable AC or DC power supplies, one AC power supply equipped by default • Forwarding performance: 162 Mpps • Switching capacity: 598 Gbit/s
 <p>S5720-56C-PWR-EI-DC</p>	<ul style="list-style-type: none"> • 48 10/100/1000 Ethernet PoE+ ports, 4 10GE SFP+ ports • One extended slot • PoE+ • Double hot swappable AC or DC power supplies, one DC power supply equipped by default • Forwarding performance: 162 Mpps • Switching capacity: 598 Gbit/s
 <p>S5720-56PC-EI-AC</p>	<ul style="list-style-type: none"> • 48 10/100/1000 Ethernet ports, 4 GE SFP ports • One extended slot • Double hot swappable AC or DC power supplies, one AC power supply equipped by default • Forwarding performance: 108 Mpps • Switching capacity: 598 Gbit/s


Card Types

The S5720-EI (C series and PC series) provides one extended slot for ES5D21X02S01 (2-port 10GE SFP+ rear interface card) for upstream connections, or ES5D21VST000 (dedicated stack card with two QSFP+ ports) for stack connection.

ES5D21X02S01 (2-Port 10 Gig SFP+ Rear Interface Card, Used in S5720-EI Series)

The ES5D21X02S01 provides two 10GE SFP+ optical ports for data access and line-rate switching. It can be installed in a rear card slot of the switch models listed in the following table.

Technical specifications of the ES5D21X02S01

Card Model	Technical Specifications	Applied Switch Model
 ES5D21X02S01	<ul style="list-style-type: none"> Physical specifications: <ul style="list-style-type: none"> Dimensions (W x D x H): 100 mm x 208 mm x 40 mm (3.94 in. x 8.19 in. x 1.57 in.) Weight: 0.78 kg (1.72 lb) Maximum power consumption: 8 W Environment parameters: <ul style="list-style-type: none"> Operating temperature: 0°C to 45°C (32°F to 113°F) Relative humidity: 5% RH to 95% RH Storage temperature: -40°C to +70°C (-40°F to +158°F) 	S5720-C-EI and S5720-PC-EI series

NOTE

Cards shipped since June 2014 have an applicability label attached at the back. Notice the card model and applicable device series on the label to avoid installing a card into an inapplicable device.


Functions and features of the ES5D21X02S01

Function and Feature	Description
Basic function	Provides two 10GE SFP+ optical ports for data access and line-rate switching.
Hot swap	Supported
Service ports for stacking	The service ports on the card can be used as stack ports.

ES5D21VST000 (Dedicated Stack Card with 2 QSFP+ Interface)

The ES5D21VST000 is a stack card that provides two QSFP+ optical ports for stack connection. It can be installed in a rear card slot of the switch models listed in the following table.

Technical specifications of the ES5D21VST000

Card Model	Technical Specifications	Applied Switch Model
 ES5D21VST000	<ul style="list-style-type: none"> Physical specifications: <ul style="list-style-type: none"> Dimensions (W x D x H): 100 mm x 208 mm x 40 mm (3.9 in. x 8.2 in. x 1.6 in.) Weight: 0.92 kg (2.03 lb) Maximum power consumption: 9 W Environment parameters: <ul style="list-style-type: none"> Operating temperature: 0°C to 45°C (32°F to 113°F) Relative humidity: 5% RH to 95% RH Storage temperature: -40°C to +70°C (-40°F to +158°F) 	S5720-C-EI and S5720-PC-EI series

NOTE


Cards shipped since June 2014 have an applicability label attached at the back. Notice the card model and applicable device series on the label to avoid installing a card into an inapplicable device.

Function and Feature	Description
Basic function	Provides two QSFP+ optical ports for setting up a stack system among multiple switches.
Hot swap	Supported

Fan Module

The following table lists the fan module applicable to the S5720-EI.



Technical specifications of the fan module available in the S5720-EI series




Fan Module	Technical Specifications	Applied Switch Model
 <p>FAN-028A-B</p>	<ul style="list-style-type: none"> • Dimensions (W x D x H): 100 mm x 220 mm x 40 mm • Number of fans: 2 • Weight: 0.34 kg • Maximum power consumption: 12 W • Maximum fan speed: 16000±10% revolutions per minute (RPM) • Maximum wind rate: 28 cubic feet per minute (CFM) • Hot swap: Supported 	<p>S5720-C-EI and S5720-PC-EI series</p> <p>NOTE</p> <p>Besides the S5720-C-EI and S5720-PC-EI series, the S5720-EI has a built-in heat dissipation system. Customers do not need to purchase fan modules.</p>



Power Supply

The following table lists the power supplies applicable to the S5720-EI.

Technical specifications of power supplies applicable to the S5720-EI series

Power Module	Technical Specifications	Applied Switch Model
 <p>ES0W2PSA0150</p>	<ul style="list-style-type: none"> • Dimensions (W x D x H): 100 mm x 205 mm x 40 mm (3.9 in. x 8.1 in. x 1.6 in.) • Weight: 0.8 kg (1.76 lb) • Rated input voltage range: 100 V AC to 240 V AC, 50/60 Hz • Maximum input voltage range: 90 V AC to 264 V AC, 47 Hz to 63 Hz • Maximum input current: 3 A • Maximum output current: 12.5 A • Rated output voltage: 12 V • Maximum output power: 150 W • Hot swap: Supported 	<ul style="list-style-type: none"> • S5720-36C-EI-AC • S5720-56C-EI-AC • S5720-56C-EI-DC • S5720-36C-EI-28S-AC • S5720-36C-EI-28S-DC • S5720-56C-EI-48S-AC • S5720-56C-EI-48S-DC • S5720-36PC-EI-AC • S5720-56PC-EI-AC
 <p>ES0W2PSD0150</p>	<ul style="list-style-type: none"> • Dimensions (W x D x H): 100 mm x 205 mm x 40 mm (3.9 in. x 8.1 in. x 1.6 in.) • Weight: 0.8 kg (1.76 lb) • Rated input voltage range: -48 V DC to -60 V DC • Maximum input voltage range: -36 V DC to -72 V DC • Maximum input current: 6 A • Maximum output current: 12.5 A • Rated output voltage: 12 V • Maximum output power: 150 W • Hot swap: Supported 	<ul style="list-style-type: none"> • S5720-36C-EI-AC • S5720-56C-EI-AC • S5720-56C-EI-DC • S5720-36C-EI-28S-AC • S5720-36C-EI-28S-DC • S5720-56C-EI-48S-AC • S5720-56C-EI-48S-DC • S5720-36PC-EI-AC • S5720-56PC-EI-AC

Power Module	Technical Specifications	Applied Switch Model
 <p>PAC-500WA-BE</p>	<ul style="list-style-type: none"> • Dimensions (W x D x H): 100 mm x 205 mm x 40 mm (3.9 in. x 8.1 in. x 1.6 in.) • Weight: 1.06 kg (2.34 lb) • Rated input voltage range: 100 V AC to 240 V AC, 50/60 Hz • Maximum input voltage range: 90 V AC to 264 V AC, 47 Hz to 63 Hz • Maximum input current: 7 A to 3.5 A • Maximum output current: <ul style="list-style-type: none"> - +12 V: 10 A - -53.5 V: 7.11 A • Maximum output power: <ul style="list-style-type: none"> - +12 V: 120 W - -53.5 V: 380 W (PoE: 369.6 W) • Hot swap: Supported 	<ul style="list-style-type: none"> • S5720-36C-PWR-EI-AC • S5720-56C-PWR-EI-DC • S5720-56C-PWR-EI-AC
 <p>PDC-650WA-BE</p>	<ul style="list-style-type: none"> • Dimensions (W x D x H): 100 mm x 205 mm x 40 mm (3.9 in. x 8.1 in. x 1.6 in.) • Weight: 0.83 kg (1.83 lb) • Rated input voltage range: -48 V DC to -60 V DC • Maximum input voltage range: -38.4 V DC to -72 V DC • Maximum input current: 20 A • Maximum output current: <ul style="list-style-type: none"> - +12 V: 22.5 A - -53.5 V: 7.11 A • Maximum output power: <ul style="list-style-type: none"> - PoE power: 369.6 W - Total power: 650 W • Hot swap: Supported 	<ul style="list-style-type: none"> • S5720-36C-PWR-EI-AC • S5720-56C-PWR-EI-DC • S5720-56C-PWR-EI-AC
 <p>W2PSA1150</p>	<ul style="list-style-type: none"> • Dimensions (W x D x H): 100.0 mm x 281.0 mm x 41.4 mm (3.9 in. x 11.1 in. x 1.63 in.) • Weight: < 1.6 kg (3.53 lb) • Rated input voltage range: 100 V AC to 240 V AC, 50/60 Hz • Maximum input voltage range: 90 V AC to 290 V AC, 45 Hz to 65 Hz • Input current: 10 A • Maximum output current: <ul style="list-style-type: none"> - +12 V: 29.17 A - -53.5 V: 14.95 A • Maximum output power: <ul style="list-style-type: none"> - PoE power: 785.4 W (220 V)/446.6 W (110 V) - Total power: 1150 W (220 V)/800 W (110 V) • Hot swap: Supported 	<ul style="list-style-type: none"> • S5720-56C-PWR-EI-AC1

Power Module	Technical Specifications	Applied Switch Model
 <p>PAC1000D5412</p>	<ul style="list-style-type: none"> • Dimensions (W x D x H): 99 mm x 204 mm x 42 mm (3.9 in. x 8.1 in. x 1.7 in.) • Weight: 1.1 kg (2.43 lb) • Rated input voltage range: <ul style="list-style-type: none"> - 100 V AC to 240 V AC, 50/60 Hz - 240 V DC • Maximum input voltage range: <ul style="list-style-type: none"> - 90 V AC to 290 V AC, 47 Hz to 63 Hz - 190 V DC to 290 V DC • Input current: <ul style="list-style-type: none"> - 100 V AC to 130 V AC: 12 A - 200 V AC to 240 V AC: 6 A - 240 V DC: 8A • Maximum output current: <ul style="list-style-type: none"> - +12 V: 20.84 A - -53.5 V: 14.58 A • Maximum output power: <ul style="list-style-type: none"> - PoE: 754.6 W - Total: 1000 W • Hot swap: Supported 	<ul style="list-style-type: none"> • S5720-56C-PWR-EI-AC1
 <p>RPS1800</p>	<ul style="list-style-type: none"> • Dimensions (W x D x H): 442.0 mm x 310.0 mm x 43.6 mm • Weight: <ul style="list-style-type: none"> - Without power modules installed: 4 kg - With one power module installed: 5.5 kg - With two power modules installed: 7 kg • Rated input voltage: 220/110 V AC, 50/60 Hz • Input voltage range: 200 V AC to 240 V AC (220 V rated voltage input)/100 V AC to 120 V AC (110 V rated voltage input), 50/60 Hz • Input current: 12 A • Maximum output current (without power modules installed): 12 V: 11.5 A • Maximum output current (with one power module installed): <ul style="list-style-type: none"> - 12 V: 11.5 A - -53.5 V: 15 A (input voltage range: 200 V AC to 240 V AC) • Maximum output current (with two power modules installed): <ul style="list-style-type: none"> - 12 V: 11.5 A - -53.5 V: 15 A output per port (input voltage range: 200 V AC to 240 V AC) - -53.5 V: 15 A output per port (input voltage range: 100 V AC to 120 V AC, two 870 W PoE power modules required) • Maximum output power (without power modules 	<p>S5720-X-EI and S5720-P-EI series</p>

Power Module	Technical Specifications	Applied Switch Model
	installed): 12 V: 140 W <ul style="list-style-type: none"> Maximum output power (with one power module installed): <ul style="list-style-type: none"> 12 V: 140 W -53.5 V: 800 W (input voltage range: 200 V AC to 240 V AC) Maximum output power (with two power modules installed): <ul style="list-style-type: none"> 12 V: 140 W -53.5 V: 1600 W (input voltage range: 200 V AC to 240 V AC) -53.5 V: 800 W (input voltage range: 100 V AC to 120 V AC, two 870 W PoE power modules required) Hot swap: Not supported 	

Some models of the S5720-EI series use built-in power supplies by default. If a switch supports pluggable power supplies, the customer can purchase the power supplies when or after purchasing the switch.

The S5720-EI supports multiple power supply options, including dual-power, PoE, and single-power.

NOTE

For detailed information about RPS1800, visit <http://support.huawei.com/enterprise/en/doc/EDOC1000013597?section=j06e&topicName=rps1800-power-supply> or contact your local Huawei sales office.

Dual-Power (Non-PoE)

Dual-power models (non-PoE) use pluggable power supplies and provide two power slots. By default, one AC power supply (ES0W2PSA0150) is equipped. When a switch has two power supplies installed, the power supplies work in 1+1 backup mode to power the switch. The switch supports dual AC power supplies, dual DC power supplies, as well as mixed insertion of AC and DC power supplies.

The following table lists the power supply options supported by the S5720-EI.

Power supply options supported by the S5720-EI series

Model	Power Supply 1	Power Supply 2
S5720-36C-EI-AC	ES0W2PSA0150 (150 W-AC) or ES0W2PSD0150 (150 W-DC)	ES0W2PSA0150 (150 W-AC) or ES0W2PSD0150 (150 W-DC)
S5720-56C-EI-AC (DC)	ES0W2PSA0150 (150 W-AC) or ES0W2PSD0150 (150 W-DC)	ES0W2PSA0150 (150 W-AC) or ES0W2PSD0150 (150 W-DC)
S5720-36C-EI-28S-AC (DC)	ES0W2PSA0150 (150 W-AC) or ES0W2PSD0150 (150 W-DC)	ES0W2PSA0150 (150 W-AC) or ES0W2PSD0150 (150 W-DC)
S5720-56C-EI-48S-AC (DC)	ES0W2PSA0150 (150 W-AC) or ES0W2PSD0150 (150 W-DC)	ES0W2PSA0150 (150 W-AC) or ES0W2PSD0150 (150 W-DC)
S5720-36PC-EI-AC	ES0W2PSA0150 (150 W-AC) or ES0W2PSD0150 (150 W-DC)	ES0W2PSA0150 (150 W-AC) or ES0W2PSD0150 (150 W-DC)
S5720-56PC-EI-AC	ES0W2PSA0150 (150 W-AC) or ES0W2PSD0150 (150 W-DC)	ES0W2PSA0150 (150 W-AC) or ES0W2PSD0150 (150 W-DC)

PoE/PoE+

PWR in the model name indicates a PoE-capable switch, which supports IEEE 802.3af-compliant PoE and 802.3at-compliant PoE+. Each port delivers 15.4 W PoE or 30 W PoE+ power capacity.

Each PoE-capable S5720-EI switch has two power slots for pluggable PoE power supplies. The following table lists the power supply options supported by PoE-capable S5720-EI models.

Power supply options supported by PoE-capable S5720-EI series

Model	Power Supply 1	Power Supply 2	PoE Power Supply	Number of PoE Ports
S5720-36C-PWR-EI-AC	500 W or 650 W	–	369.6 W	<ul style="list-style-type: none"> PoE (15.4 W): 24 PoE+ (30 W): 12
	P500 W or 650 W	500 W or 650 W	739.2 W	<ul style="list-style-type: none"> PoE (15.4 W): 28 PoE+ (30 W): 24
S5720-56C-PWR-EI-AC (DC)	500 W or 650 W	–	369.6 W	<ul style="list-style-type: none"> PoE (15.4 W): 24 PoE+ (30 W): 12
	500 W or 650 W	500 W or 650 W	739.2 W	<ul style="list-style-type: none"> PoE (15.4 W): 48 PoE+ (30 W): 24
S5720-56C-PWR-EI-AC1	1150 W (220 V)	–	785.4 W	<ul style="list-style-type: none"> PoE (15.4 W): 48 PoE+ (30 W): 26
	1150 W (220 V)	1150 W (220 V)	1440 W	<ul style="list-style-type: none"> PoE (15.4 W): 48 PoE+ (30 W): 48
	1150 W (110 V)	–	446.6 W	<ul style="list-style-type: none"> PoE (15.4 W): 29 PoE+ (30 W): 14
	1150 W (110 V)	1150 W (110 V)	893.2 W	<ul style="list-style-type: none"> PoE (15.4 W): 48 PoE+ (30 W): 29
	1000 W (220 V)	–	754.6 W	<ul style="list-style-type: none"> PoE (15.4 W): 48 PoE+ (30 W): 25
	1000 W (220 V)	1000 W (220 V)	1440 W	<ul style="list-style-type: none"> PoE (15.4 W): 48 PoE+ (30 W): 48
	1000 W (110 V)	–	754.6 W	<ul style="list-style-type: none"> PoE (15.4 W): 48 PoE+ (30 W): 25
	1000 W (110 V)	1000 W (110 V)	1440 W	<ul style="list-style-type: none"> PoE (15.4 W): 48 PoE+ (30 W): 48
	1000 W (220 V)	1150 W (220 V)	1440 W	<ul style="list-style-type: none"> PoE (15.4 W): 48 PoE+ (30 W): 48
	1150 W (220 V)	1000 W (220 V)	1440 W	<ul style="list-style-type: none"> PoE (15.4 W): 48 PoE+ (30 W): 48
	1000 W (110 V)	1150 W (110 V)	893.2 W	<ul style="list-style-type: none"> PoE (15.4 W): 48 PoE+ (30 W): 29
	1150 W (110 V)	1000 W (110 V)	893.2 W	<ul style="list-style-type: none"> PoE (15.4 W): 48 PoE+ (30 W): 29

NOTE

When a switch has two power supplies installed, the two power supplies work in redundancy mode to provide power for the switch and in load balancing mode to provide power for powered devices (PDs).


Single-Power

Single-power models use a built-in AC power supply and support RPS1800. Single-power models include S5720-32P-EI-AC, S5720-32X-EI-AC, S5720-32X-EI-24S-AC, S5720-32X-EI-24S-DC, S5720-50X-EI-AC, S5720-50X-EI-DC, S5720-50X-EI-46S-AC, S5720-50X-EI-46S-DC, S5720-52X-EI-AC, and S5720-52P-EI-AC.

An RPS1800 is a redundant power supply system that provides power redundancy for the connected switches to ensure uninterrupted services. When the internal power supply of a switch fails, the RPS1800 provides power to the switch immediately, improving system reliability. The following figure shows how to connect an RPS1800 to a switch.

NOTE

The RPS1800 only provides power redundancy for switches and cannot power on a switch directly.



The RPS1800 can connect to a maximum of six switches and ensures seamless failover for at most one switch when the internal power supply of the switch fails.

When the internal power supply of the switch powered by the RPS1800 recovers, the RPS1800 immediately restores to backup state.

Among the six DC output ports, OUT1 has the highest priority, and the other five ports have the same priority. When the RPS1800 connects to six switches, the switch connected to OUT1 preferentially receives power from the RPS1800.

Product Features and Highlights

Easy Operations and Maintenance (O&M)

- The S5720-EI models with power sockets on the front panel can be installed in a 300 mm deep cabinet and maintained from the front panel. This simplifies equipment O&M and allows more flexible cabinet deployment. The small-sized cabinets can be placed against a wall or back to back to save space in the equipment room.
- The S5720-EI allows management personnel to remotely switch on the SYS indicator on the front panel. After configuration commands are used, the SYS indicator quickly blinks within a certain period, helping the management personnel locate the device in the equipment room quickly and efficiently.
- The S5720-EI supports Super Virtual Fabric (SVF), which virtualizes the "Core/Aggregation switches + Access switches + APs" structure into a single logical device. The S5720-EI enables the simplest network management solution in the industry. It allows plug-and-play of access switches and APs. In addition, the S5720-EI supports service configuration templates. The templates are configured on core devices and automatically delivered to access devices, enabling centralized control, simplified service configuration, and flexible configuration modification. The S5720-EI functions as a client in an SVF system.
- The S5720-EI supports EasyOperation, a solution that provides zero-touch deployment, replacement of faulty devices without additional configuration, USB-based deployment, batch configuration, and batch remote upgrade. The EasyOperation

solution facilitates device deployment, upgrade, service provisioning, and other management and maintenance operations, greatly reducing O&M costs. The S5720-EI can be managed using Simple Network Management Protocol (SNMP) v1/v2c/v3, command line interface (CLI), web-based network management system, or Secure Shell (SSH) V2.0. Additionally, it supports remote network monitoring (RMON), multiple log hosts, port traffic statistics collection, and network quality analysis, which facilitate network optimization and reconstruction.

- The S5720-EI supports Two-Way Active Measurement Protocol (TWAMP) to accurately check any IP link and obtain the entire network's IP performance. This protocol eliminates the need of using a dedicated probe or a proprietary protocol.

Intelligent O&M

- The S5720-EI provides telemetry technology to collect device data in real time and send the data to Huawei campus network analyzer CampusInsight. The CampusInsight analyzes network data based on the intelligent fault identification algorithm, accurately displays the real-time network status, effectively demarcates and locates faults in a timely manner, and identifies network problems that affect user experience, accurately guaranteeing user experience.
- The S5720-EI supports a variety of intelligent O&M features for audio and video services, including the enhanced Media Delivery Index (eMDI). With this eMDI function, the switch can function as a monitored node to periodically conduct statistics and report audio and video service indicators to the CampusInsight platform. In this way, the CampusInsight platform can quickly demarcate audio and video service quality faults based on the results of multiple monitored nodes.

Multiple Reliability Mechanisms

- The S5720-EI supports intelligent stack (iStack). This technology can virtualize up to nine physical switches into a single logical switch. Member switches in a stack implement redundancy backup to improve device reliability and use inter-device link aggregation to improve link reliability. iStack ensures path failover within 200 milliseconds and implements hitless master/backup switchover. iStack provides strong network expansion capability, enables easy increase of ports, bandwidth, and processing capacity of a stack, and simplifies configuration and management.
- The S5720-EI is equipped with two removable power supplies that can work in 1+1 redundancy backup mode. Mixed installation of AC and DC power supplies is supported, allowing for flexible configuration of AC and DC power supplies according to service requirements. The S5720-EI provides two removable fan modules. The fan speed can be adjusted according to working temperatures of the device, improving device reliability.
- In addition to traditional STP, RSTP, and MSTP, the S5720-EI supports Huawei-developed Smart Ethernet Protection (SEP) technology and the latest Ethernet Ring Protection Switching (ERPS) standard. SEP is a ring protection protocol specific to the Ethernet link layer, and applies to various ring network topologies, such as open ring topology, closed ring topology, and cascading ring topology. This protocol is reliable and easy to maintain, and implements fast protection switching within 50 ms. ERPS is defined in ITU-T G.8032. It implements millisecond-level protection switching based on traditional Ethernet MAC and bridging functions.
- The S5720-EI supports Smart Link and Virtual Router Redundancy Protocol (VRRP), which implement backup of uplinks. One S5720-EI switch can connect to multiple aggregation switches through multiple links, significantly improving reliability of access devices.
- In addition, the S5720-EI provides multiple connection fault detection mechanisms, including Ethernet OAM (IEEE 802.3ah/802.1ag/ITU Y.1731) and Bidirectional Forwarding Detection (BFD).

Enhanced Service Processing Capability and Comprehensive Security Control Mechanisms

- The S5720-EI supports the multi-VPN-instance CE (MCE) function, which allows connection of users in different VPNs. The switch supports large multi-instance routing tables to isolate users in different VPNs. Users in multiple VPNs connect to a provider edge (PE) device through the same physical port on the switch, which reduces the cost on VPN network deployment. The S5720-EI supports Multiprotocol Label Switching (MPLS) L3VPN, MPLS L2VPN (VPWS\VPWS), MPLS-TE, and MPLS QoS. It is one of a few cost-effective MPLS-capable fixed switches.
- With enhanced network admission control (NAC) functions, the S5720-EI supports 802.1X authentication, MAC address authentication, Portal authentication, and hybrid authentication, and can dynamically delivery user policies such as VLANs, QoS policies, and access control lists (ACLs). It also supports user management based on user groups. You can specify authentication-free IP network segments and enable redirection of HTTP connection requests to realize fast deployment of clients. If clients do not support HTTP access, the S5720-EI can trigger Portal authentication for the clients.
- The S5720-EI provides a series of mechanisms to defend against DoS and user-targeted attacks. DoS attacks are targeted at switches and include SYN flood, Land, Smurf, and ICMP flood attacks. User-targeted attacks include bogus DHCP server attacks, IP/MAC address spoofing, DHCP request flood, and change of the DHCP CHADDR value.

- The S5720-EI sets up and maintains a DHCP snooping binding table, and discards the packets that do not match the table entries. You can specify DHCP snooping trusted and untrusted ports to ensure that users connect only to the authorized DHCP server.
- The S5720-EI supports strict ARP learning, which protects a network against ARP spoofing attacks to ensure normal network access.

Enhanced QoS Control Mechanism

- The S5720-EI provides excellent QoS capabilities and supports queue scheduling and congestion control algorithms. Additionally, it adopts innovative priority queuing and multi-level scheduling mechanisms to implement fine-grained scheduling of data flows, meeting service quality requirements of different user terminals and services.
- The S5720-EI implements complex traffic classification based on packet information, such as the 5-tuple, IP preference, ToS, DSCP, IP protocol type, ICMP type, TCP source port, VLAN ID, Ethernet protocol type, and CoS. ACLs can be applied to the inbound or outbound direction of a port.
- The S5720-EI supports flow-based two-rate three-color CAR. Each port supports eight priority queues, multiple queue scheduling algorithms, such as WRR, DRR, SP, WRR+SP, and DRR+SP, and WRED that is a congestion avoidance algorithm. All of these features ensure high-quality voice, video, and data services.

Mature IPv6 Technologies

- The S5720-EI uses the mature, stable VRP software platform and supports IPv4/IPv6 dual stacks, IPv6 routing protocols (RIPng, OSPFv3, BGP4+, and IS-ISv6), and IPv6 over IPv4 tunnels (including manual, 6-to-4, and ISATAP tunnels). With these IPv6 features, the S5720-EI can be deployed on a pure IPv4 network, a pure IPv6 network, or a shared IPv4/IPv6 network, helping achieve IPv4-to-IPv6 transition.

OPS

- Open Programmability System (OPS) is an open programmable system based on the Python language. IT administrators can program the O&M functions of a switch through Python scripts to quickly innovate functions and implement intelligent O&M.

Perpetual PoE

- When a PoE switch is rebooted after the software version is upgraded, the power supply to PDs is not interrupted. This capability ensures that PDs are not powered off during the switch reboot.

NOTE

For more information about PoE, visit

<https://e.huawei.com/en/material/onLineView?materialid=e28cc3ad158140e8af1547bc510ecd34>

Product Specifications

Functions and Features

The following table lists the functions and features available on the S5720-EI.

Function and feature metrics for the S5720-EI series

Function and Feature		Description	S5720-P-EI series	S5720-X-EI series	S5720-C-EI series	S5720-PC-EI series
Ethernet features	Ethernet basics	Full-duplex, half-duplex, and auto-negotiation	Yes	Yes	Yes	Yes
		Rate auto-negotiation on an interface	Yes	Yes	Yes	Yes
		Flow control on an interface	Yes	Yes	Yes	Yes
		Jumbo frames	Yes	Yes	Yes	Yes

Function and Feature		Description	S5720-P-EI series	S5720-X-EI series	S5720-C-EI series	S5720-PC-EI series
		Link aggregation	Yes	Yes	Yes	Yes
		Load balancing among links of a trunk	Yes	Yes	Yes	Yes
		Transparent transmission of Layer 2 protocol packets	Yes	Yes	Yes	Yes
		Device Link Detection Protocol (DLDP)	Yes	Yes	Yes	Yes
		Link Layer Discovery Protocol (LLDP)	Yes	Yes	Yes	Yes
		Link Layer Discovery Protocol-Media Endpoint Discovery (LLDP-MED)	Yes	Yes	Yes	Yes
		Interface isolation	Yes	Yes	Yes	Yes
		Broadcast traffic suppression on an interface	Yes	Yes	Yes	Yes
		Multicast traffic suppression on an interface	Yes	Yes	Yes	Yes
		Unknown unicast traffic suppression on an interface	Yes	Yes	Yes	Yes
		VLAN broadcast traffic suppression	Yes	Yes	Yes	Yes
		VLAN multicast traffic suppression	Yes	Yes	Yes	Yes
		VLAN unknown unicast traffic suppression	Yes	Yes	Yes	Yes
	VLAN	VLAN specification	4094	4094	4094	4094
	VLANIF interface specification	1024	1024	1024	1024	
	Access mode	Yes	Yes	Yes	Yes	
	Trunk mode	Yes	Yes	Yes	Yes	
	Hybrid mode	Yes	Yes	Yes	Yes	
	QinQ mode	Yes	Yes	Yes	Yes	
	Default VLAN	Yes	Yes	Yes	Yes	
	VLAN assignment based on interfaces	Yes	Yes	Yes	Yes	
	VLAN assignment based on protocols	Yes	Yes	Yes	Yes	
	VLAN assignment based on IP subnets	Yes	Yes	Yes	Yes	
VLAN assignment based on MAC addresses	Yes	Yes	Yes	Yes		

Function and Feature		Description	S5720-P-EI series	S5720-X-EI series	S5720-C-EI series	S5720-PC-EI series	
		VLAN assignment based on MAC address + IP address	Yes	Yes	Yes	Yes	
		VLAN assignment based on MAC address + IP address + interface number	Yes	Yes	Yes	Yes	
		Adding double VLAN tags to packets based on interfaces	Yes	Yes	Yes	Yes	
		Super-VLAN	Yes	Yes	Yes	Yes	
		Super-VLAN specification	256	256	256	256	
		Sub-VLAN	Yes	Yes	Yes	Yes	
		Sub-VLAN specification	1K	1K	1K	1K	
		VLAN mapping	Yes	Yes	Yes	Yes	
		Selective QinQ	Yes	Yes	Yes	Yes	
		MUX VLAN	Yes	Yes	Yes	Yes	
		Voice VLAN	Yes	Yes	Yes	Yes	
		Guest VLAN	Yes	Yes	Yes	Yes	
		GVRP	GARP	Yes	Yes	Yes	Yes
			GVRP	Yes	Yes	Yes	Yes
		VCMP	VCMP	Yes	Yes	Yes	Yes
		MAC	MAC address	64K	64K	64K	64K
			Automatic learning of MAC addresses	Yes	Yes	Yes	Yes
			Automatic aging of MAC addresses	Yes	Yes	Yes	Yes
			Static, dynamic, and blackhole MAC address entries	Yes	Yes	Yes	Yes
			Interface-based MAC address learning limiting	Yes	Yes	Yes	Yes
	Sticky MAC		Yes	Yes	Yes	Yes	
	MAC address flapping detection		Yes	Yes	Yes	Yes	
	Configuring MAC address learning priorities for interfaces		Yes	Yes	Yes	Yes	
	MAC address spoofing defense		Yes	Yes	Yes	Yes	
	Port bridge		Yes	Yes	Yes	Yes	
	ARP	Static ARP	Yes	Yes	Yes	Yes	

Function and Feature		Description	S5720-P-EI series	S5720-X-EI series	S5720-C-EI series	S5720-PC-EI series
		Dynamic ARP	Yes	Yes	Yes	Yes
		ARP entry	12K	12K	12K	12K
		ARP aging detection	Yes	Yes	Yes	Yes
		Intra-VLAN proxy ARP	Yes	Yes	Yes	Yes
		Inter-VLAN proxy ARP	Yes	Yes	Yes	Yes
		Routed proxy ARP	Yes	Yes	Yes	Yes
		Multi-egress-interface ARP	Yes	Yes	Yes	Yes
Ethernet loop protection	MSTP	STP	Yes	Yes	Yes	Yes
		RSTP	Yes	Yes	Yes	Yes
		MSTP	Yes	Yes	Yes	Yes
		VBST	Yes	Yes	Yes	Yes
		BPDU protection	Yes	Yes	Yes	Yes
		Root protection	Yes	Yes	Yes	Yes
		Loop protection	Yes	Yes	Yes	Yes
		Defense against TC BPDU attacks	Yes	Yes	Yes	Yes
	Loopback detection	Loop detection on an interface	Yes	Yes	Yes	Yes
	SEP	SEP	Yes	Yes	Yes	Yes
	Smart Link	Smart Link	Yes	Yes	Yes	Yes
		Smart Link multi-instance	Yes	Yes	Yes	Yes
		Monitor Link	Yes	Yes	Yes	Yes
	RRPP	RRPP	Yes	Yes	Yes	Yes
		Single RRPP ring	Yes	Yes	Yes	Yes
		Tangent RRPP ring	Yes	Yes	Yes	Yes
		Intersecting RRPP ring	Yes	Yes	Yes	Yes
		Hybrid networking of RRPP rings and other ring networks	Yes	Yes	Yes	Yes
	ERPS	G.8032 v1	Yes	Yes	Yes	Yes
		G.8032 v2	Yes	Yes	Yes	Yes
		ERPS semi-ring topology	Yes	Yes	Yes	Yes
		ERPS closed-ring topology	Yes	Yes	Yes	Yes
	IPv4/IPv6 forwarding	IPv4 and unicast routing	IPv4 static routing	Yes	Yes	Yes
VRF			Yes	Yes	Yes	Yes

Function and Feature		Description	S5720-P-EI series	S5720-X-EI series	S5720-C-EI series	S5720-PC-EI series
		DHCP client	Yes	Yes	Yes	Yes
		DHCP server	Yes	Yes	Yes	Yes
		DHCP relay	Yes	Yes	Yes	Yes
		DHCP policy VLAN	Yes	Yes	Yes	Yes
		URPF check	Yes	Yes	Yes	Yes
		Routing policies	Yes	Yes	Yes	Yes
		IPv4 routes	16K	16K	16K	16K
		RIPv1	Yes	Yes	Yes	Yes
		RIPv2	Yes	Yes	Yes	Yes
		OSPF	Yes	Yes	Yes	Yes
		BGP	Yes	Yes	Yes	Yes
		MBGP	Yes	Yes	Yes	Yes
		IS-IS	Yes	Yes	Yes	Yes
		Policy-based routing (PBR)	Yes	Yes	Yes	Yes
	Multicast routing features	IGMPv1/v2/v3	Yes	Yes	Yes	Yes
		PIM-DM	Yes	Yes	Yes	Yes
		PIM-SM	Yes	Yes	Yes	Yes
		MSDP	Yes	Yes	Yes	Yes
		IPv4 multicast routes	4K	4K	4K	4K
		IPv6 multicast routes	2K	2K	2K	2K
		Multicast routing policies	Yes	Yes	Yes	Yes
	RPF	Yes	Yes	Yes	Yes	
	IPv6 features	IPv6 protocol stack	Yes	Yes	Yes	Yes
		ND	Yes	Yes	Yes	Yes
		ND entry	8K	8K	8K	8K
		ND snooping	Yes	Yes	Yes	Yes
		DHCPv6 snooping	Yes	Yes	Yes	Yes
		RIPng	Yes	Yes	Yes	Yes
		DHCPv6 server	Yes	Yes	Yes	Yes
		DHCPv6 relay	Yes	Yes	Yes	Yes
		OSPFv3	Yes	Yes	Yes	Yes
		BGP4+	Yes	Yes	Yes	Yes
		IS-IS for IPv6	Yes	Yes	Yes	Yes

Function and Feature		Description	S5720-P-EI series	S5720-X-EI series	S5720-C-EI series	S5720-PC-EI series
		IPv6 routes	8K	8K	8K	8K
		VRRP6	Yes	Yes	Yes	Yes
		MLDv1/v2	Yes	Yes	Yes	Yes
		PIM-DM for IPv6	Yes	Yes	Yes	Yes
		PIM-SM for IPv6	Yes	Yes	Yes	Yes
	IPv6 transition technology	IPv6 manual tunneling	Yes	Yes	Yes	Yes
Layer 2 multicast features	-	IGMPv1/v2/v3 snooping	Yes	Yes	Yes	Yes
		IGMP snooping proxy	Yes	Yes	Yes	Yes
		MLD snooping	Yes	Yes	Yes	Yes
		Multicast traffic suppression	Yes	Yes	Yes	Yes
		Inter-VLAN multicast replication	Yes	Yes	Yes	Yes
MPLS & VPN	MPLS basic functions	LDP protocol	Yes	Yes	Yes	Yes
		Double MPLS labels	Yes	Yes	Yes	Yes
		Mapping from 802.1p priorities to EXP priorities in MPLS packets	Yes	Yes	Yes	Yes
		Mapping from DSCP priorities to EXP priorities in MPLS packets	Yes	Yes	Yes	Yes
	MPLS TE	MPLS-TE tunnel establishment	Yes	Yes	Yes	Yes
		MPLS-TE tunnel specification	256	256	256	256
		MPLS-TE protection group	Yes	Yes	Yes	Yes
	VPN	MCE	Yes	Yes	Yes	Yes
		GRE tunneling	Yes	Yes	Yes	Yes
		GRE tunnel specification	512	512	512	512
		VLL	Yes	Yes	Yes	Yes
		PWE3	Yes	Yes	Yes	Yes
		VPLS	Yes	Yes	Yes	Yes
		MPLS L3VPN	Yes	Yes	Yes	Yes
IPSec Efficient VPN	Yes	Yes	Yes	Yes		
Device reliability	BFD	Single-hop BFD	Yes	Yes	Yes	Yes
		BFD for static routes	Yes	Yes	Yes	Yes
		BFD for OSPF	Yes	Yes	Yes	Yes

Function and Feature		Description	S5720-P-EI series	S5720-X-EI series	S5720-C-EI series	S5720-PC-EI series
		BFD for IS-IS	Yes	Yes	Yes	Yes
		BFD for BGP	Yes	Yes	Yes	Yes
		BFD for PIM	Yes	Yes	Yes	Yes
		BFD for VRRP	Yes	Yes	Yes	Yes
	Stacking	Stack card-based stacking	No	No	Yes	Yes
		Stack card-based stacking bandwidth (Unidirectional)	No	No	Up to 42 Gbit/s	Up to 42 Gbit/s
		Service interface-based stacking	Yes	Yes	Yes	Yes
		Service interface-based stacking bandwidth (Unidirectional)	Up to 40 Gbit/s	Up to 40 Gbit/s	Up to 40 Gbit/s	Up to 40 Gbit/s
		Maximum number of stacked devices	9	9	9	9
	VRRP	VRRP standard protocol	Yes	Yes	Yes	Yes
Ethernet OAM	EFM (802.3ah)	Automatic discovery of links	Yes	Yes	Yes	Yes
		Link fault detection	Yes	Yes	Yes	Yes
		Link troubleshooting	Yes	Yes	Yes	Yes
		Remote loopback	Yes	Yes	Yes	Yes
	CFM (802.1ag)	Software-level CCM	Yes	Yes	Yes	Yes
		802.1ag MAC ping	Yes	Yes	Yes	Yes
		802.1ag MAC trace	Yes	Yes	Yes	Yes
	OAM association	Association between 802.1ag and 802.3ah	Yes	Yes	Yes	Yes
	Y.1731	Unidirectional delay and jitter measurement	Yes	Yes	Yes	Yes
		Bidirectional delay and jitter measurement	Yes	Yes	Yes	Yes
QoS features	Traffic classification	Traffic classification based on ACLs	Yes	Yes	Yes	Yes
		Configuring traffic classification priorities	Yes	Yes	Yes	Yes
		Matching the simple domains of packets	Yes	Yes	Yes	Yes
	Traffic behavior	Traffic filtering	Yes	Yes	Yes	Yes
		Traffic policing (CAR)	Yes	Yes	Yes	Yes
		Modifying the packet priorities	Yes	Yes	Yes	Yes
		Modifying the simple domains	Yes	Yes	Yes	Yes

Function and Feature		Description	S5720-P-EI series	S5720-X-EI series	S5720-C-EI series	S5720-PC-EI series	
		of packets					
		Modifying the packet VLANs	Yes	Yes	Yes	Yes	
	Traffic shaping	Traffic shaping on an egress interface	Yes	Yes	Yes	Yes	
		Traffic shaping on queues on an interface	Yes	Yes	Yes	Yes	
	Congestion avoidance	Weighted Random Early Detection (WRED) on interfaces	Yes	Yes	Yes	Yes	
		WRED on queues	Yes	Yes	Yes	Yes	
		Tail drop	Yes	Yes	Yes	Yes	
	Congestion management	Priority Queuing (PQ)	Yes	Yes	Yes	Yes	
		Weighted Deficit Round Robin (WDRR)	Yes	Yes	Yes	Yes	
		PQ+WDRR	Yes	Yes	Yes	Yes	
		Weighted Round Robin (WRR)	Yes	Yes	Yes	Yes	
		PQ+WRR	Yes	Yes	Yes	Yes	
	HQoS	HQoS	Yes	Yes	Yes	Yes	
	ACL	Packet filtering at Layer 2 to Layer 4	Number of rules per IPv4 ACL	4K	4K	4K	4K
			Number of rules per IPv6 ACL	2K	2K	2K	2K
Basic IPv4 ACL			Yes	Yes	Yes	Yes	
Advanced IPv4 ACL			Yes	Yes	Yes	Yes	
Basic IPv6 ACL			Yes	Yes	Yes	Yes	
Advanced IPv6 ACL			Yes	Yes	Yes	Yes	
Layer 2 ACL			Yes	Yes	Yes	Yes	
User group ACL			Yes	Yes	Yes	Yes	
User-defined ACL			Yes	Yes	Yes	Yes	
Configuration and maintenance	Login and configuration management	Command line interface (CLI)-based configuration	Yes	Yes	Yes	Yes	
		Console terminal service	Yes	Yes	Yes	Yes	
		Telnet terminal service	Yes	Yes	Yes	Yes	
		SSH v1.5	Yes	Yes	Yes	Yes	
		SSH v2.0	Yes	Yes	Yes	Yes	
		SNMP-based NMS for unified configuration	Yes	Yes	Yes	Yes	
		Web page-based	Yes	Yes	Yes	Yes	

Function and Feature		Description	S5720-P-EI series	S5720-X-EI series	S5720-C-EI series	S5720-PC-EI series
		configuration and management				
		EasyDeploy (client)	Yes	Yes	Yes	Yes
		EasyDeploy (commander)	Yes	Yes	Yes	Yes
		SVF	Yes	Yes	Yes	Yes
		Cloud management	Yes	Yes	Yes	Yes
		OPS	Yes	Yes	Yes	Yes
	File system	Directory and file management	Yes	Yes	Yes	Yes
		File upload and download	Yes	Yes	Yes	Yes
	Monitoring and maintenance	eMDI	Yes	Yes	Yes	Yes
		Hardware monitoring	Yes	Yes	Yes	Yes
		Log information output	Yes	Yes	Yes	Yes
		Alarm information output	Yes	Yes	Yes	Yes
		Debugging information output	Yes	Yes	Yes	Yes
		Port mirroring	Yes	Yes	Yes	Yes
		Flow mirroring	Yes	Yes	Yes	Yes
		Remote mirroring	Yes	Yes	Yes	Yes
		Energy saving	Yes	Yes	Yes	Yes
	Version upgrade	Version upgrade	Yes	Yes	Yes	Yes
		Version rollback	Yes	Yes	Yes	Yes
	Security	ARP security	ARP packet rate limiting	Yes	Yes	Yes
ARP anti-spoofing			Yes	Yes	Yes	Yes
Association between ARP and STP			Yes	Yes	Yes	Yes
ARP gateway anti-collision			Yes	Yes	Yes	Yes
Dynamic ARP Inspection (DAI)			Yes	Yes	Yes	Yes
Static ARP Inspection (SAI)			Yes	Yes	Yes	Yes
Egress ARP Inspection (EAI)			Yes	Yes	Yes	Yes
IP security		ICMP attack defense	Yes	Yes	Yes	Yes
		IPSG for IPv4	Yes	Yes	Yes	Yes
		IPSG user capacity	3000	3000	3000	3000
		IPSG for IPv6	Yes	Yes	Yes	Yes
		IPSGv6 user capacity	1500	1500	1500	1500

Function and Feature		Description	S5720-P-EI series	S5720-X-EI series	S5720-C-EI series	S5720-PC-EI series	
	Local attack defense	CPU attack defense	Yes	Yes	Yes	Yes	
	MFF	MFF	Yes	Yes	Yes	Yes	
	DHCP snooping	DHCP snooping	Yes	Yes	Yes	Yes	
		Option 82 function	Yes	Yes	Yes	Yes	
		Dynamic rate limiting for DHCP packets	Yes	Yes	Yes	Yes	
	Attack defense	Defense against malformed packet attacks	Yes	Yes	Yes	Yes	
		Defense against UDP flood attacks	Yes	Yes	Yes	Yes	
		Defense against TCP SYN flood attacks	Yes	Yes	Yes	Yes	
		Defense against ICMP flood attacks	Yes	Yes	Yes	Yes	
		Defense against packet fragment attacks	Yes	Yes	Yes	Yes	
		Local URPF	Yes	Yes	Yes	Yes	
	User access and authentication	AAA	Local authentication	Yes	Yes	Yes	Yes
			Local authorization	Yes	Yes	Yes	Yes
RADIUS authentication			Yes	Yes	Yes	Yes	
RADIUS authorization			Yes	Yes	Yes	Yes	
RADIUS accounting			Yes	Yes	Yes	Yes	
HWTACACS authentication			Yes	Yes	Yes	Yes	
HWTACACS authorization			Yes	Yes	Yes	Yes	
HWTACACS accounting			Yes	Yes	Yes	Yes	
NAC		802.1X authentication	Yes	Yes	Yes	Yes	
		MAC address authentication	Yes	Yes	Yes	Yes	
		Portal authentication	Yes	Yes	Yes	Yes	
		Hybrid authentication	Yes	Yes	Yes	Yes	
MACSec		MACSec	Yes	Yes	Yes	Yes	
Policy association		Functioning as the access device	Yes	Yes	Yes	Yes	
Network management	-	Ping	Yes	Yes	Yes	Yes	
		Tracert	Yes	Yes	Yes	Yes	
		NQA	Yes	Yes	Yes	Yes	

Function and Feature		Description	S5720-P-EI series	S5720-X-EI series	S5720-C-EI series	S5720-PC-EI series
		NTP	Yes	Yes	Yes	Yes
		sFlow	Yes	Yes	Yes	Yes
		SNMP v1	Yes	Yes	Yes	Yes
		SNMP v2c	Yes	Yes	Yes	Yes
		SNMP v3	Yes	Yes	Yes	Yes
		HTTP	Yes	Yes	Yes	Yes
		HTTPS	Yes	Yes	Yes	Yes
		RMON	Yes	Yes	Yes	Yes
		RMON2	Yes	Yes	Yes	Yes
		NETCONF/YANG	Yes	Yes	Yes	Yes
Interoperability	-	VLAN-based Spanning Tree (VBST)	Yes	Yes	Yes	Yes
		Link-type Negotiation Protocol (LNP)	Yes	Yes	Yes	Yes
		VLAN Central Management Protocol (VCMP)	Yes	Yes	Yes	Yes

NOTE

This content is applicable only to regions outside mainland China. Huawei reserves the right to interpret this content.

Hardware Specifications

The following table lists hardware specifications of the S5720-EI.

[Hardware specifications of the S5720-36C-EI or S5720-36PC-EI series](#)

Item		S5720-36C-EI-28S-AC S5720-36C-EI-28S-DC	S5720-36C-EI-AC	S5720-36C-PWR-EI-AC	S5720-36PC-EI-AC
Physical specifications	Chassis dimensions (W x D x H, mm)	442 x 420 x 44.4	442 x 420 x 44.4	442 x 420 x 44.4	442 x 420 x 44.4
	Chassis height	1 U	1 U	1 U	1 U
	Chassis weight (full configuration weight, including weight of packaging materials)	<ul style="list-style-type: none"> S5720-36C-EI-28S-AC: 9.88 kg S5720-36C-EI-28S-DC: 9.68 kg 	9.76 kg	9.92 kg	9.76 kg
Fixed port	GE port	24	24	24	32

Item		S5720-36C-EI-28S-AC S5720-36C-EI-28S-DC	S5720-36C-EI-AC	S5720-36C-PWR-EI-AC	S5720-36PC-EI-AC
	10GE port	4	4	4	NA
Flexible card	Card slot	1	1	1	1
	Card type	<ul style="list-style-type: none"> 2-port 10GE SFP+ interface card 2-port QSFP+ dedicated stack card 	<ul style="list-style-type: none"> 2-port 10GE SFP+ interface card 2-port QSFP+ dedicated stack card 	<ul style="list-style-type: none"> 2-port 10GE SFP+ interface card 2-port QSFP+ dedicated stack card 	<ul style="list-style-type: none"> 2-port 10GE SFP+ interface card 2-port QSFP+ dedicated stack card
	Card specification	For details about cards, see the section Card Types .	For details about cards, see the section Card Types .	For details about cards, see the section Card Types .	For details about cards, see the section Card Types .
Management port	ETH management port	Supported	Supported	Supported	Supported
	Console port (RJ45)	Supported	Supported	Supported	Supported
	Console port (Mini USB)	Supported	Supported	Supported	Supported
	USB port	USB 2.0	USB 2.0	USB 2.0	USB 2.0
CPU	Frequency	1 GHz	1 GHz	1 GHz	1 GHz
	Cores	2	2	2	2
Memory	Memory (RAM)	2 GB	2 GB	2 GB	2 GB
	Flash memory	Hardware: 512 MB, of which 340 MB is available for users	Hardware: 512 MB, of which 340 MB is available for users	Hardware: 512 MB, of which 340 MB is available for users	Hardware: 512 MB, of which 340 MB is available for users
Power supply system	Power supply type	<ul style="list-style-type: none"> 150 W AC (pluggable) 150 W DC (pluggable) 	<ul style="list-style-type: none"> 150 W AC (pluggable) 150 W DC (pluggable) 	<ul style="list-style-type: none"> 500 W AC (pluggable) 650 W DC (pluggable) 	<ul style="list-style-type: none"> 150 W AC (pluggable) 150 W DC (pluggable)
	Power supply specification	For details about power supplies, see the section Power Supply .	For details about power supplies, see the section Power Supply .	For details about power supplies, see the section Power Supply .	For details about power supplies, see the section Power Supply .
	Power supply redundancy	1+1	1+1	1+1	1+1
	Rated voltage range	<ul style="list-style-type: none"> AC: 100 V AC to 240 V AC; 50/60 Hz DC: -48 V DC to -60 V DC 	<ul style="list-style-type: none"> AC: 100 V AC to 240 V AC; 50/60 Hz DC: -48 V DC to -60 V DC 	<ul style="list-style-type: none"> AC: 100 V AC to 240 V AC; 50/60 Hz DC: -48 V DC to -60 V DC 	<ul style="list-style-type: none"> AC: 100 V AC to 240 V AC; 50/60 Hz DC: -48 V DC to -60 V DC
	Maximum voltage range	<ul style="list-style-type: none"> AC: 90 V AC to 264 V AC; 47-63 	<ul style="list-style-type: none"> AC: 90 V AC to 264 V AC; 47-63 	<ul style="list-style-type: none"> AC: 90 V AC to 264 V AC; 47-63 	<ul style="list-style-type: none"> AC: 90 V AC to 264 V AC; 47-63

Item		S5720-36C-EI-28S-AC S5720-36C-EI-28S-DC	S5720-36C-EI-AC	S5720-36C-PWR-EI-AC	S5720-36PC-EI-AC
		Hz • DC: -36 V DC to -72 V DC	Hz • DC: -36 V DC to -72 V DC	Hz • DC: -38.4 V DC to -72 V DC	Hz • DC: -36 V DC to -72 V DC
	Maximum input current	• 150 W AC: 3 A • 150 W DC: 6 A	• 150 W AC: 3 A • 150 W DC: 6 A	• 500 W AC: 7 A • 650 W DC: 20 A	• 150 W AC: 3 A • 150 W DC: 6 A
	Maximum power consumption of the device	83.9 W	75.8 W	• Without PDs: 78 W • With PDs: 864.3 W (PDs: 739.2 W)	74.6 W
	Power consumption in the case of 30% traffic load ¹	• 47.86 W (without cards) • 55.35 W (with a 2-port 10GE optical card) • 60.25 W (with a 2-port QSFP+ stack card)	• 39.5 W (without cards) • 7.28 W (with a 2-port 10GE optical card) • 52.17 W (with a 2-port QSFP+ stack card)	• 48.45 W (without cards) • 56.14 W (with a 2-port 10GE optical card) • 60.76 W (with a 2-port QSFP+ stack card)	• 39.5 W (without cards) • 47.28 W (with a 2-port 10GE optical card) • 52.17 W (with a 2-port QSFP+ stack card)
	Power consumption in the case of 100% traffic load ¹	• 56.65 W (without cards) • 64.06 W (with a 2-port 10GE optical card) • 68.65 W (with a 2-port QSFP+ stack card)	• 46.4 W (without cards) • 54.06 W (with a 2-port 10GE optical card) • 59.36 W (with a 2-port QSFP+ stack card)	• 54.15 W (without cards) • 61.85 W (with a 2-port 10GE optical card) • 66.64 W (with a 2-port QSFP+ stack card)	• 46.4 W (without cards) • 54.06 W (with a 2-port 10GE optical card) • 59.36 W (with a 2-port QSFP+ stack card)
Heat dissipation system	Heat dissipation mode	Air-cooled heat dissipation and intelligent fan speed adjustment	Air-cooled heat dissipation and intelligent fan speed adjustment	Air-cooled heat dissipation and intelligent fan speed adjustment	Air-cooled heat dissipation and intelligent fan speed adjustment
	Number of fan modules	Pluggable dual fans	Pluggable dual fans	Pluggable dual fans	Pluggable dual fans
	Airflow	Air flows in from the left and right sides as well as the front panel, and exhausts from the rear panel	Air flows in from the left and right sides as well as the front panel, and exhausts from the rear panel	Air flows in from the left and right sides as well as the front panel, and exhausts from the rear panel	Air flows in from the left and right sides as well as the front panel, and exhausts from the rear panel
	Maximum heat dissipation of the device (BTU/hour)	286	259	• Without PoE output: 266 • Full-load PoE: 2950	259
Environment parameters	Long-term operating temperature	• 0-1800 m: 0°C to 45°C • 1800-5000 m: The operating temperature	• 0-1800 m: 0°C to 45°C • 1800-5000 m: The operating temperature	• 0-1800 m: 0°C to 45°C • 1800-5000 m: The operating temperature	• 0-1800 m: 0°C to 45°C • 1800-5000 m: The operating temperature

Item	S5720-36C-EI-28S-AC S5720-36C-EI-28S-DC	S5720-36C-EI-AC	S5720-36C-PWR-EI-AC	S5720-36PC-EI-AC
	decreases 1°C every time the altitude increases 220 m.	decreases 1°C every time the altitude increases 220 m.	decreases 1°C every time the altitude increases 220 m.	decreases 1°C every time the altitude increases 220 m.
Short-term operating temperature	<ul style="list-style-type: none"> 0-1800 m: -5°C to +50°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. <p>NOTE Short term indicates that the successive operating time is no more than 96 hours, the total operating time is no more than 360 hours, or the number of times the operating temperature is over 45°C is no more than 15 in a year.</p>	<ul style="list-style-type: none"> 0-1800 m: -5°C to +50°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. <p>NOTE Short term indicates that the successive operating time is no more than 96 hours, the total operating time is no more than 360 hours, or the number of times the operating temperature is over 45°C is no more than 15 in a year.</p>	<ul style="list-style-type: none"> 0-1800 m: -5°C to +50°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. <p>NOTE Short term indicates that the successive operating time is no more than 96 hours, the total operating time is no more than 360 hours, or the number of times the operating temperature is over 45°C is no more than 15 in a year.</p>	<ul style="list-style-type: none"> 0-1800 m: -5°C to +50°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. <p>NOTE Short term indicates that the successive operating time is no more than 96 hours, the total operating time is no more than 360 hours, or the number of times the operating temperature is over 45°C is no more than 15 in a year.</p>
Storage temperature	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C
Relative humidity	5%–95% (non-condensing)	5%–95% (non-condensing)	5%–95% (non-condensing)	5%–95% (non-condensing)
Operating altitude	<ul style="list-style-type: none"> AC: 5000 m DC: 2000 m 	<ul style="list-style-type: none"> AC: 5000 m DC: 2000 m 	<ul style="list-style-type: none"> AC: 5000 m DC: 2000 m 	<ul style="list-style-type: none"> AC: 5000 m DC: 2000 m
Noise under normal temperature (sound power)	51.2 dB(A)	51.2 dB(A)	53.7 dB(A)	51.2 dB(A)
Noise under high temperature (sound power)	71 dB(A)	71 dB(A)	71.3 dB(A)	71 dB(A)
Noise under normal temperature (sound pressure)	37.5 dB(A)	37.5 dB(A)	40.0 dB(A)	37.5 dB(A)

Item		S5720-36C-EI-28S-AC S5720-36C-EI-28S-DC	S5720-36C-EI-AC	S5720-36C-PWR-EI-AC	S5720-36PC-EI-AC
	Surge protection specification (RJ45 service port)	±8 kV in common mode	±8 kV in common mode	±8 kV in common mode	±8 kV in common mode
	Surge protection specification (power port)	<ul style="list-style-type: none"> AC power interface: ±6 kV in differential or common mode DC power interface: ±1 kV in differential; ±2 kV in common mode 	<ul style="list-style-type: none"> AC power interface: ±6 kV in differential or common mode DC power interface: ±1 kV in differential; ±2 kV in common mode 	<ul style="list-style-type: none"> AC power interface: ±6 kV in differential or common mode DC power interface: ±2 kV in differential; ±4 kV in common mode 	<ul style="list-style-type: none"> AC power interface: ±6 kV in differential or common mode DC power interface: ±1 kV in differential; ±2 kV in common mode
Reliability	MTBF (year) ²	<ul style="list-style-type: none"> Without cards: 85.45 With a 2-port 10GE SFP+ card: 78.2 With a stack card: 76.05 	<ul style="list-style-type: none"> Without cards: 80.05 With a 2-port 10GE SFP+ card: 73.65 With a stack card: 71.74 	<ul style="list-style-type: none"> Without cards: 60.72 With a 2-port 10GE SFP+ card: 56.97 With a stack card: 55.82 	<ul style="list-style-type: none"> Without cards: 80.05 With a 2-port 10GE SFP+ card: 73.65 With a stack card: 71.74
	MTTR (hour)	2	2	2	2
	Availability	> 0.99999	> 0.99999	> 0.99999	> 0.99999
Certification		<ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification <p>For details about certifications, see the section Safety and Regulatory Compliance.</p>	<ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification <p>For details about certifications, see the section Safety and Regulatory Compliance.</p>	<ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification <p>For details about certifications, see the section Safety and Regulatory Compliance.</p>	<ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification <p>For details about certifications, see the section Safety and Regulatory Compliance.</p>

Hardware specifications of the S5720-56C-EI or S5720-56PC-EI series

Item		S5720-56C-EI-48S-AC S5720-56C-EI-48S-DC	S5720-56C-EI-AC S5720-56C-EI-DC	S5720-56C-PWR-EI-AC S5720-56C-PWR-EI-DC	S5720-56C-PWR-EI-AC1	S5720-56PC-EI-AC
Physical specifications	Chassis dimensions (W x D x H, mm)	442 x 420 x 44.4	442 x 420 x 44.4	442 x 420 x 44.4	442 x 507 x 44.4	442 x 420 x 44.4
	Chassis height	1 U	1 U	1 U	1 U	1 U
	Chassis weight (full)	<ul style="list-style-type: none"> S5720-56C-EI-48S-AC: 10.10 	<ul style="list-style-type: none"> S5720-56C-EI- 	<ul style="list-style-type: none"> S5720-56C-PWR- 	10.9 kg	9.92 kg

Item		S5720-56C-EI-48S-AC S5720-56C-EI-48S-DC	S5720-56C-EI-AC S5720-56C-EI-DC	S5720-56C-PWR-EI-AC S5720-56C-PWR-EI-DC	S5720-56C-PWR-EI-AC1	S5720-56PC-EI-AC
	configuration weight, including weight of packaging materials)	kg <ul style="list-style-type: none"> S5720-56C-EI-48S-DC: 9.9 kg 	AC: 9.92 kg <ul style="list-style-type: none"> S5720-56C-EI-DC: 9.72 kg 	EI-AC: 10.32 kg <ul style="list-style-type: none"> S5720-56C-PWR-EI-DC: 10.3 kg 		
Fixed port	GE port	48	48	48	48	52
	10GE port	4	4	4	4	NA
Flexible card	Card slot	1	1	1	1	1
	Card type	<ul style="list-style-type: none"> 2-port 10GE SFP+ interface card 2-port QSFP+ dedicated stack card 	<ul style="list-style-type: none"> 2-port 10GE SFP+ interface card 2-port QSFP+ dedicated stack card 	<ul style="list-style-type: none"> 2-port 10GE SFP+ interface card 2-port QSFP+ dedicated stack card 	<ul style="list-style-type: none"> 2-port 10GE SFP+ interface card 2-port QSFP+ dedicated stack card 	<ul style="list-style-type: none"> 2-port 10GE SFP+ interface card 2-port QSFP+ dedicated stack card
	Card specification	For details about cards, see the section Card Types .	For details about cards, see the section Card Types .	For details about cards, see the section Card Types .	For details about cards, see the section Card Types .	For details about cards, see the section Card Types .
Management port	ETH management port	Supported	Supported	Supported	Supported	Supported
	Console port (RJ45)	Supported	Supported	Supported	Supported	Supported
	Console port (Mini USB)	Supported	Supported	Supported	Supported	Supported
	USB port	USB 2.0	USB 2.0	USB 2.0	USB 2.0	USB 2.0
CPU	Frequency	1 GHz	1 GHz	1 GHz	1 GHz	1 GHz
	Cores	2	2	2	2	2
Memory	Memory (RAM)	2 GB	2 GB	2 GB	2 GB	2 GB
	Flash memory	Hardware: 512 MB, of which 340 MB is available for users	Hardware: 512 MB, of which 340 MB is available for users	Hardware: 512 MB, of which 340 MB is available for users	Hardware: 512 MB, of which 340 MB is available for users	Hardware: 512 MB, of which 340 MB is available for users
Power supply system	Power supply type	<ul style="list-style-type: none"> 150 W AC (pluggable) 150 W DC (pluggable) 	<ul style="list-style-type: none"> 150 W AC (pluggable) 150 W DC (pluggable) 	<ul style="list-style-type: none"> 500 W AC (pluggable) 650 W DC (pluggable) 	<ul style="list-style-type: none"> 1150 W AC (pluggable) 1000 W AC 	<ul style="list-style-type: none"> 150 W AC (pluggable) 150 W DC (pluggable)

Item	S5720-56C-EI-48S-AC S5720-56C-EI-48S-DC	S5720-56C-EI-AC S5720-56C-EI-DC	S5720-56C-PWR-EI-AC S5720-56C-PWR-EI-DC	S5720-56C-PWR-EI-AC1	S5720-56PC-EI-AC
				(pluggable)	
Power supply specification	For details about power supplies, see the section Power Supply .	For details about power supplies, see the section Power Supply .	For details about power supplies, see the section Power Supply .	For details about power supplies, see the section Power Supply .	For details about power supplies, see the section Power Supply .
Power supply redundancy	1+1	1+1	1+1	1+1	1+1
Rated voltage range	<ul style="list-style-type: none"> AC: 100 V AC to 240 V AC; 50/60 Hz DC: -48 V DC to -60 V DC 	<ul style="list-style-type: none"> AC: 100 V AC to 240 V AC; 50/60 Hz DC: -48 V DC to -60 V DC 	<ul style="list-style-type: none"> AC: 100 V AC to 240 V AC; 50/60 Hz DC: -48 V DC to -60 V DC 	AC: 100 V AC to 240 V AC; 50/60 Hz	<ul style="list-style-type: none"> AC: 100 V AC to 240 V AC; 50/60 Hz DC: -48 V DC to -60 V DC
Maximum voltage range	<ul style="list-style-type: none"> AC: 90 V AC to 264 V AC; 47-63 Hz DC: -36 V DC to -72 V DC 	<ul style="list-style-type: none"> AC: 90 V AC to 264 V AC; 47-63 Hz DC: -36 V DC to -72 V DC 	<ul style="list-style-type: none"> AC: 90 V AC to 264 V AC; 47-63 Hz DC: -38.4 V DC to -72 V DC 	AC: 90 V AC to 264 V AC; 47-63 Hz	<ul style="list-style-type: none"> AC: 90 V AC to 264 V AC; 47-63 Hz DC: -36 V DC to -72 V DC
Maximum input current	<ul style="list-style-type: none"> 150 W AC: 3 A 150 W DC: 6 A 	<ul style="list-style-type: none"> 150 W AC: 3 A 150 W DC: 6 A 	<ul style="list-style-type: none"> 500 W AC: 7 A 650 W DC: 20 A 	<ul style="list-style-type: none"> 1150 W AC: 10 A 1000 W AC: 12A 	<ul style="list-style-type: none"> 150 W AC: 3 A 150 W DC: 6 A
Maximum power consumption of the device	104 W	86.9 W	<ul style="list-style-type: none"> Without PDs: 91.6 W With PDs: 889.4 W (PDs: 739.2 W) 	<ul style="list-style-type: none"> Without PDs: 91.6 W With PDs: 1564.8 W (PDs: 1440 W) 	85.7 W
Power consumption in the case of 30% traffic load ¹	<ul style="list-style-type: none"> 68.82 W (without cards) 76.55 W (with a 2-port 10GE optical card) 81.23 W (with a 2-port QSFP+ stack card) 	<ul style="list-style-type: none"> 40.45 W (without cards) 47.78 W (with a 2-port 10GE optical card) 52.87 W (with a 2-port QSFP+ stack card) 	S5720-56C-PWR-EI-AC: <ul style="list-style-type: none"> 53.5 W (without cards) 61.12 W (with a 2-port 10GE optical card) 65.85 W (with a 2-port QSFP+ stack card) 	<ul style="list-style-type: none"> 53.5 W (without cards) 61.12 W (with a 2-port 10GE optical card) 65.85 W (with a 2-port QSFP+ stack card) 	<ul style="list-style-type: none"> 40.45 W (without cards) 47.78 W (with a 2-port 10GE optical card) 52.87 W (with a 2-port QSFP+ stack card)

Item		S5720-56C-EI-48S-AC S5720-56C-EI-48S-DC	S5720-56C-EI-AC S5720-56C-EI-DC	S5720-56C-PWR-EI-AC S5720-56C-PWR-EI-DC	S5720-56C-PWR-EI-AC1	S5720-56PC-EI-AC
				S5720-56C-PWR-EI-DC: <ul style="list-style-type: none"> • 56.68 W (without cards) • 63.63 W (with a 2-port 10GE optical card) • 68.56 W (with a 2-port QSFP+ stack card) 		
	Power consumption in the case of 100% traffic load ¹	<ul style="list-style-type: none"> • 70.25 W (without cards) • 77.65 W (with a 2-port 10GE optical card) • 82.67 W (with a 2-port QSFP+ stack card) 	<ul style="list-style-type: none"> • 60.1 W (without cards) • 67.72 W (with a 2-port 10GE optical card) • 72.55 W (with a 2-port QSFP+ stack card) 	S5720-56C-PWR-EI-AC: <ul style="list-style-type: none"> • 62.24 W (without cards) • 69.75 W (with a 2-port 10GE optical card) • 74.55 W (with a 2-port QSFP+ stack card) S5720-56C-PWR-EI-DC: <ul style="list-style-type: none"> • 69.23 W (without cards) • 76.23 W (with a 2-port 10GE optical card) • 81.48 W (with a 2-port QSFP+ stack card) 	<ul style="list-style-type: none"> • 62.24 W (without cards) • 69.75 W (with a 2-port 10GE optical card) • 74.55 W (with a 2-port QSFP+ stack card) 	<ul style="list-style-type: none"> • 60.1 W (without cards) • 67.72 W (with a 2-port 10GE optical card) • 72.55 W (with a 2-port QSFP+ stack card)
Heat dissipation system	Heat dissipation mode	Air-cooled heat dissipation and intelligent fan speed adjustment	Air-cooled heat dissipation and intelligent fan speed adjustment	Air-cooled heat dissipation and intelligent fan speed adjustment	Air-cooled heat dissipation and intelligent fan speed adjustment	Air-cooled heat dissipation and intelligent fan speed adjustment

Item		S5720-56C-EI-48S-AC S5720-56C-EI-48S-DC	S5720-56C-EI-AC S5720-56C-EI-DC	S5720-56C-PWR-EI-AC S5720-56C-PWR-EI-DC	S5720-56C-PWR-EI-AC1	S5720-56PC-EI-AC
	Number of fan modules	Pluggable dual fans	Pluggable dual fans	Pluggable dual fans	Pluggable dual fans	Pluggable dual fans
	Airflow	Air flows in from the left and right sides as well as the front panel, and exhausts from the rear panel	Air flows in from the left and right sides as well as the front panel, and exhausts from the rear panel	Air flows in from the left and right sides as well as the front panel, and exhausts from the rear panel	Air flows in from the left and right sides as well as the front panel, and exhausts from the rear panel	Air flows in from the left and right sides as well as the front panel, and exhausts from the rear panel
	Maximum heat dissipation of the device (BTU/hour)	355	297	<ul style="list-style-type: none"> Without PoE output: 313 Full-load PoE: 3035 Without PoE output: 334 Full-load PoE: 3116 	<ul style="list-style-type: none"> Without PoE output: 313 Full-load PoE: 5341 	297
Environment parameters	Long-term operating temperature	<ul style="list-style-type: none"> 0-1800 m: 0°C to 45°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. 	<ul style="list-style-type: none"> 0-1800 m: 0°C to 45°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. 	<ul style="list-style-type: none"> 0-1800 m: 0°C to 45°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. 	<ul style="list-style-type: none"> 0-1800 m: 0°C to 45°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. 	<ul style="list-style-type: none"> 0-1800 m: 0°C to 45°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m.
	Short-term operating temperature	<ul style="list-style-type: none"> 0-1800 m: -5°C to +50°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. <p>NOTE Short term indicates that the successive operating time is no more than 96 hours, the total</p>	<ul style="list-style-type: none"> 0-1800 m: -5°C to +50°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. <p>NOTE Short term indicates</p>	<ul style="list-style-type: none"> 0-1800 m: -5°C to +50°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. <p>NOTE Short term indicates</p>	<ul style="list-style-type: none"> 0-1800 m: -5°C to +50°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. <p>NOTE Short term indicates</p>	<ul style="list-style-type: none"> 0-1800 m: -5°C to +50°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. <p>NOTE Short term indicates that the</p>

Item	S5720-56C-EI-48S-AC	S5720-56C-EI-AC	S5720-56C-PWR-EI-AC	S5720-56C-PWR-EI-AC1	S5720-56PC-EI-AC	
	S5720-56C-EI-48S-DC	S5720-56C-EI-DC	S5720-56C-PWR-EI-DC			
	operating time is no more than 360 hours, or the number of times the operating temperature is over 45°C is no more than 15 in a year.	that the successive operating time is no more than 96 hours, the total operating time is no more than 360 hours, or the number of times the operating temperature is over 45°C is no more than 15 in a year.	that the successive operating time is no more than 96 hours, the total operating time is no more than 360 hours, or the number of times the operating temperature is over 45°C is no more than 15 in a year.	that the successive operating time is no more than 96 hours, the total operating time is no more than 360 hours, or the number of times the operating temperature is over 45°C is no more than 15 in a year.	that the successive operating time is no more than 96 hours, the total operating time is no more than 360 hours, or the number of times the operating temperature is over 45°C is no more than 15 in a year.	successive operating time is no more than 96 hours, the total operating time is no more than 360 hours, or the number of times the operating temperature is over 45°C is no more than 15 in a year.
Storage temperature	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C	
Relative humidity	5%-95% (non-condensing)	5%-95% (non-condensing)	5%-95% (non-condensing)	5%-95% (non-condensing)	5%-95% (non-condensing)	
Operating altitude	<ul style="list-style-type: none"> AC: 5000 m DC: 2000 m 	<ul style="list-style-type: none"> AC: 5000 m DC: 2000 m 	5000 m	5000 m	<ul style="list-style-type: none"> AC: 5000 m DC: 2000 m 	
Noise under normal temperature (sound power)	51.2 dB(A)	51.2 dB(A)	53.7 dB(A)	61.7 dB(A)	51.2 dB(A)	
Noise under high temperature (sound power)	71 dB(A)	71 dB(A)	71.3 dB(A)	72.1 dB(A)	71 dB(A)	
Noise under normal temperature (sound pressure)	37.5 dB(A)	37.5 dB(A)	40.0 dB(A)	47.9 dB(A)	37.5 dB(A)	
Surge protection specification (RJ45 service port)	NA	±8 kV in common mode	±8 kV in common mode	±8 kV in common mode	±8 kV in common mode	
Surge protection specification (power port)	<ul style="list-style-type: none"> AC power port: ±6 kV in differential or common mode 	<ul style="list-style-type: none"> AC power port: ±6 kV in differential 	<ul style="list-style-type: none"> AC power port: ±6 kV in differential 	<ul style="list-style-type: none"> 1150 W AC: ±2 kV in differential 	<ul style="list-style-type: none"> AC power port: ±6 kV in differential or common 	

Item		S5720-56C-EI-48S-AC S5720-56C-EI-48S-DC	S5720-56C-EI-AC S5720-56C-EI-DC	S5720-56C-PWR-EI-AC S5720-56C-PWR-EI-DC	S5720-56C-PWR-EI-AC1	S5720-56PC-EI-AC
		<ul style="list-style-type: none"> DC power port: ±1 kV in differential mode; ±2 kV in common mode 	<ul style="list-style-type: none"> or common mode DC power port: ±1 kV in differential mode; ±2 kV in common mode 	<ul style="list-style-type: none"> or common mode DC power port: ±2 kV in differential mode; ±4 kV in common mode 	<ul style="list-style-type: none"> mode; ±4 kV in common mode 1000 W AC: ±6 kV in differential mode; ±6 kV in common mode 	<ul style="list-style-type: none"> mode DC power port: ±1 kV in differential mode; ±2 kV in common mode
Reliability	MTBF (year) ²	<ul style="list-style-type: none"> Without cards: 73.91 With a 2-port 10GE SFP+ card: 68.42 With a stack card: 66.77 	<ul style="list-style-type: none"> Without cards: 71.18 With a 2-port 10GE SFP+ card: 66.07 With a stack card: 64.53 	<ul style="list-style-type: none"> Without cards: 51.34 With a 2-port 10GE SFP+ card: 48.63 With a stack card: 47.79 	<ul style="list-style-type: none"> Without cards: 51.34 With a 2-port 10GE SFP+ card: 48.63 With a stack card: 47.79 	<ul style="list-style-type: none"> Without cards: 71.18 With a 2-port 10GE SFP+ card: 66.07 With a stack card: 64.53
	MTTR (hour)	2	2	2	2	2
	Availability	> 0.99999	> 0.99999	> 0.99999	> 0.99999	> 0.99999
Certification		<ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification <p>For details about certifications, see the section Safety and Regulatory Compliance.</p>	<ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification <p>For details about certifications, see the section Safety and Regulatory Compliance.</p>	<ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification <p>For details about certifications, see the section Safety and Regulatory Compliance.</p>	<ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification <p>For details about certifications, see the section Safety and Regulatory Compliance.</p>	<ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification <p>For details about certifications, see the section Safety and Regulatory Compliance.</p>

Hardware specifications of the S5720-X-EI series

Item		S5720-32X-EI-24S-AC S5720-32X-EI-24S-DC	S5720-32X-EI-AC	S5720-50X-EI-46S-AC S5720-50X-EI-46S-DC	S5720-50X-EI-AC S5720-50X-EI-DC	S5720-52X-EI-AC
Physical specifications	Chassis dimensions (W)	442 x 220 x 43.6 (front-access)	442 x 220 x 43.6 (front-	442 x 220 x 43.6 (front-	442 x 220 x 43.6 (front-	442 x 220 x 43.6

Item		S5720-32X-EI-24S-AC	S5720-32X-EI-AC	S5720-50X-EI-46S-AC	S5720-50X-EI-AC	S5720-52X-EI-AC
		S5720-32X-EI-24S-DC		S5720-50X-EI-46S-DC	S5720-50X-EI-DC	
	x D x H, mm)		access)	access)	access)	
	Chassis height	1 U	1 U	1 U	1 U	1 U
	Chassis weight (full configuration weight, including weight of packaging materials)	<ul style="list-style-type: none"> S5720-32X-EI-24S-AC: 4.44 kg S5720-32X-EI-24S-DC: 4.21 kg 	4.44 kg	<ul style="list-style-type: none"> S5720-50X-EI-46S-AC: 4.97 kg S5720-50X-EI-46S-DC: 4.74 kg 	<ul style="list-style-type: none"> S5720-50X-EI-AC: 4.88 kg S5720-50X-EI-DC: 4.65 kg 	4.66 kg
Fixed port	GE port	28	28	46	48	48
	10GE port	4	4	4	4	4
	Dedicated stack port	2	2	2	2	2
Management port	ETH management port	Supported	Supported	NA	NA	Supported
	Console port (RJ45)	Supported	Supported	Supported	Supported	Supported
	Console port (Mini USB)	Supported	Supported	NA	NA	Supported
	USB port	USB 2.0	USB 2.0	USB 2.0	USB 2.0	USB 2.0
CPU	Frequency	1 GHz	1 GHz	1 GHz	1 GHz	1 GHz
	Cores	2	2	2	2	2
Memory	Memory (RAM)	2 GB	2 GB	2 GB	2 GB	2 GB
	Flash memory	Hardware: 512 MB, of which 340 MB is available for users	Hardware: 512 MB, of which 340 MB is available for users	Hardware: 512 MB, of which 340 MB is available for users	Hardware: 512 MB, of which 340 MB is available for users	Hardware: 512 MB, of which 340 MB is available for users
Power supply system	Power supply type	<ul style="list-style-type: none"> S5720-32X-EI-24S-AC: AC (fixed) S5720-32X-EI-24S-DC: DC (fixed) 	AC (fixed)	<ul style="list-style-type: none"> S5720-50X-EI-46S-AC: AC (fixed) S5720-50X-EI-46S-DC: DC (fixed) 	<ul style="list-style-type: none"> S5720-50X-EI-AC: AC (fixed) S5720-50X-EI-DC: DC (fixed) 	AC (fixed)
	Power supply redundancy	Built-in single power supply and RPS in 6:1 mode	Built-in single power supply and RPS in 6:1 mode	Built-in single power supply and RPS in 6:1 mode	Built-in single power supply and RPS in 6:1 mode	Built-in single power supply and RPS in 6:1 mode
	RPS	Supported	Supported	Supported	Supported	Supported

Item		S5720-32X-EI-24S-AC	S5720-32X-EI-AC	S5720-50X-EI-46S-AC	S5720-50X-EI-AC	S5720-52X-EI-AC
		S5720-32X-EI-24S-DC		S5720-50X-EI-46S-DC	S5720-50X-EI-DC	
	Rated voltage range	<ul style="list-style-type: none"> S5720-32X-EI-24S-AC: 100 V AC to 240 V AC, 50/60 Hz S5720-32X-EI-24S-DC: -48 V DC to -60 V DC 	AC: 100 V AC to 240 V AC, 50/60 Hz	<ul style="list-style-type: none"> S5720-50X-EI-46S-AC: 100 V AC to 240 V AC, 50/60 Hz S5720-50X-EI-46S-DC: -48 V DC to -60 V DC 	<ul style="list-style-type: none"> S5720-50X-EI-AC: 100 V AC to 240 V AC, 50/60 Hz S5720-50X-EI-DC: -48 V DC to -60 V DC 	AC: 100 V AC to 240 V AC, 50/60 Hz
	Maximum voltage range	<ul style="list-style-type: none"> S5720-32X-EI-24S-AC: 90 V AC to 264 V AC; 47-63 Hz S5720-32X-EI-24S-DC: -36 V DC to -72 V DC 	AC: 90 V AC to 264 V AC; 47-63 Hz	<ul style="list-style-type: none"> S5720-50X-EI-46S-AC: 90 V AC to 264 V AC; 47-63 Hz S5720-50X-EI-46S-DC: -36 V DC to -72 V DC 	<ul style="list-style-type: none"> S5720-50X-EI-AC: 90 V AC to 264 V AC; 47-63 Hz S5720-50X-EI-DC: -36 V DC to -72 V DC 	AC: 90 V AC to 264 V AC; 47-63 Hz
	Maximum input current	3 A	2 A	3 A	3 A	3 A
	Maximum power consumption of the device	58.9 W	51.9 W	81.5 W	55.3 W	61.5 W
	Power consumption in the case of 30% traffic load ¹	55.46 W	40.85 W	73.75 W	47.45 W	52.25 W
	Power consumption in the case of 100% traffic load ¹	56.5 W	45.9 W	76.5 W	49.7 W	56.65 W
Heat dissipation system	Heat dissipation mode	Air-cooled heat dissipation and intelligent fan speed adjustment	Air-cooled heat dissipation and intelligent fan speed adjustment	Air-cooled heat dissipation and intelligent fan speed adjustment	Air-cooled heat dissipation and intelligent fan speed adjustment	Air-cooled heat dissipation and intelligent fan speed adjustment
	Number of fan modules	1	1	2	1	1
	Airflow	Air flows in from the left side and front	Air flows in from the left	Air flows in from the left	Air flows in from the left	Air flows in from the left side and

Item		S5720-32X-EI-24S-AC	S5720-32X-EI-AC	S5720-50X-EI-46S-AC	S5720-50X-EI-AC	S5720-52X-EI-AC
		S5720-32X-EI-24S-DC		S5720-50X-EI-46S-DC	S5720-50X-EI-DC	
		panel and exhausts from the right side	side and front panel and exhausts from the right side	side and front panel and exhausts from the right side	side and front panel and exhausts from the right side	front panel and exhausts from the right side
	Maximum heat dissipation of the device (BTU/hour)	201	177	278	189	210
Environment parameters	Long-term operating temperature	<ul style="list-style-type: none"> 0-1800 m: 0°C to 45°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. 	<ul style="list-style-type: none"> 0-1800 m: 0°C to 45°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. 	<ul style="list-style-type: none"> 0-1800 m: 0°C to 45°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. 	<ul style="list-style-type: none"> 0-1800 m: 0°C to 45°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. 	<ul style="list-style-type: none"> 0-1800 m: 0°C to 45°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m.
	Storage temperature	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C
	Relative humidity	5%-95% (non-condensing)	5%-95% (non-condensing)	5%-95% (non-condensing)	5%-95% (non-condensing)	5%-95% (non-condensing)
	Operating altitude	<ul style="list-style-type: none"> S5720-32X-EI-24S-AC: 5000 m S5720-32X-EI-24S-DC: 2000 m 	5000 m	<ul style="list-style-type: none"> S5720-50X-EI-46S-AC: 5000 m S5720-50X-EI-46S-DC: 2000 m 	<ul style="list-style-type: none"> S5720-50X-EI-AC: 5000 m S5720-50X-EI-DC: 2000 m 	5000 m
	Noise under normal temperature (sound power)	49.3 dB(A)	49.3 dB(A)	51.1 dB(A)	49.3 dB(A)	49.3 dB(A)
	Noise under high temperature (sound power)	69.2 dB(A)	69.2 dB(A)	72.3 dB(A)	69.2 dB(A)	69.2 dB(A)
	Noise under normal temperature (sound pressure)	35.9 dB(A)	35.9 dB(A)	37.6 dB(A)	35.9 dB(A)	35.9 dB(A)
	Surge protection	±8kV in common mode	±8kV in common mode	NA	±8kV in common mode	±8kV in common mode

Item		S5720-32X-EI-24S-AC S5720-32X-EI-24S-DC	S5720-32X-EI-AC	S5720-50X-EI-46S-AC S5720-50X-EI-46S-DC	S5720-50X-EI-AC S5720-50X-EI-DC	S5720-52X-EI-AC
	specification (RJ45 service port)					
	Surge protection specification (power port)	<ul style="list-style-type: none"> S5720-32X-EI-24S-AC: ±6kV in differential mode, ±6kV in common mode S5720-32X-EI-24S-DC: ±1kV in differential mode, ±2kV in common mode 	±6kV in differential mode, ±6kV in common mode	<ul style="list-style-type: none"> S5720-50X-EI-46S-AC: ±6kV in differential mode, ±6kV in common mode S5720-50X-EI-46S-DC: ±1kV in differential mode, ±2kV in common mode 	<ul style="list-style-type: none"> S5720-50X-EI-AC: ±6kV in differential mode, ±6kV in common mode S5720-50X-EI-DC: ±1kV in differential mode, ±2kV in common mode 	±6kV in differential mode, ±6kV in common mode
Reliability	MTBF (year) ²	82.54	80.32	67.59	74.31	73.12
	MTTR (hour)	2	2	2	2	2
	Availability	> 0.99999	> 0.99999	> 0.99999	> 0.99999	> 0.99999
Certification		<ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification <p>For details about certifications, see the section Safety and Regulatory Compliance.</p>	<ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification <p>For details about certifications, see the section Safety and Regulatory Compliance.</p>	<ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification <p>For details about certifications, see the section Safety and Regulatory Compliance.</p>	<ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification <p>For details about certifications, see the section Safety and Regulatory Compliance.</p>	<ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification <p>For details about certifications, see the section Safety and Regulatory Compliance.</p>

Hardware specifications of the S5720-P-EI series

Item		S5720-32P-EI-AC	S5720-52P-EI-AC
Physical specifications	Chassis dimensions (W x D x H, mm)	442 x 220 x 43.6 (front-access)	442 x 220 x 43.6
	Chassis height	1 U	1 U
	Chassis weight (full)	4.44 kg	4.66 kg

Item		S5720-32P-EI-AC	S5720-52P-EI-AC
	configuration weight, including weight of packaging materials)		
Fixed port	GE port	32	52
	Dedicated stack port	2	2
Management port	ETH management port	Supported	Supported
	Console port (RJ45)	Supported	Supported
	Console port (Mini USB)	Supported	Supported
	USB port	USB 2.0	USB 2.0
CPU	Frequency	1 GHz	1 GHz
	Cores	2	2
Memory	Memory (RAM)	2 GB	2 GB
	Flash memory	Hardware: 512 MB, of which 340 MB is available for users	Hardware: 512 MB, of which 340 MB is available for users
Power supply system	Power supply type	AC (fixed)	AC (fixed)
	Power supply redundancy	Built-in single power supply and RPS in 6:1 mode	Built-in single power supply and RPS in 6:1 mode
	RPS	Supported	Supported
	Rated voltage range	AC: 100 V AC to 240 V AC, 50/60 Hz	AC: 100 V AC to 240 V AC, 50/60 Hz
	Maximum voltage range	AC: 90 V AC to 264 V AC; 47-63 Hz	AC: 90 V AC to 264 V AC; 47-63 Hz
	Maximum input current	2 A	3 A
	Maximum power consumption of the device	50.7 W	60.3 W
	Power consumption in the case of 30% traffic load ¹	39.75 W	51.14 W
	Power consumption in the case of 100% traffic load ¹	44.7 W	55.65 W
Heat dissipation system	Heat dissipation mode	Air-cooled heat dissipation and intelligent fan speed adjustment	Air-cooled heat dissipation and intelligent fan speed adjustment
	Number of fan modules	1	1
	Airflow	Air flows in from the left side and front panel and exhausts from the right side	Air flows in from the left side and front panel and exhausts from the right side
	Maximum heat dissipation of the device (BTU/hour)	173	206
Environment parameters	Long-term operating temperature	<ul style="list-style-type: none"> 0-1800 m: 0°C to 45°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m. 	<ul style="list-style-type: none"> 0-1800 m: 0°C to 45°C 1800-5000 m: The operating temperature decreases 1°C every time the altitude increases 220 m.
	Storage temperature	-40°C to +70°C	-40°C to +70°C

Item		S5720-32P-EI-AC	S5720-52P-EI-AC
	Relative humidity	5%-95% (non-condensing)	5%-95% (non-condensing)
	Operating altitude	5000 m	5000 m
	Noise under normal temperature (sound power)	49.3 dB(A)	49.3 dB(A)
	Noise under high temperature (sound power)	69.2 dB(A)	69.2 dB(A)
	Noise under normal temperature (sound pressure)	35.9 dB(A)	35.9 dB(A)
	Surge protection specification (RJ45 service port)	±8kV in common mode	±8kV in common mode
	Surge protection specification (power port)	±6kV in differential mode, ±6kV in common mode	±6kV in differential mode, ±6kV in common mode
Reliability	MTBF (year) ²	80.32	73.12
	MTTR (hour)	2	2
	Availability	> 0.99999	> 0.99999
Certification	<ul style="list-style-type: none"> • EMC certification • Safety certification • Manufacturing certification For details about certifications, see the section Safety and Regulatory Compliance .	<ul style="list-style-type: none"> • EMC certification • Safety certification • Manufacturing certification For details about certifications, see the section Safety and Regulatory Compliance .	

 **NOTE**

1: The power consumption under different load conditions is calculated according to the ATIS standard. Additionally, the EEE function is enabled and there is no PoE power output.


2: The reliability parameter values are calculated based on the typical configuration of the device. The parameter values vary according to the modules configured by the customer.

Networking and Applications

Large-scale Enterprise Networks


The S5720-EI can be used as an access switch in a large-sized enterprise network or as an aggregation device in a small- or medium-sized campus network. It supports link aggregation and dual-homing to improve network reliability.

Position of the S5720-EI on a large-scale enterprise network



Data Center Networks

As shown in the following figure, the S5720-EI can be used in a data center to connect to gigabit servers. In a data center, S5720-EI switches connect to upstream aggregation switches through bundled links. If many servers are deployed in a rack, multiple S5720-EI switches can set up a stack system to simplify management and improve network reliability.



Product Accessories

Optical Modules and Fibers

The S5720-EI supports the following GE, 10GE, and 40GE optical modules:

- GE: 100 m electrical, 500 m optical multi-mode, 10/40/80/100 km optical single-mode, two pairs of bidirectional optical modules (10/40 km)
- 10GE: 100/220/300 m SFP+ multi-mode, 1.4/10/40/80 km optical SFP+

Optical fibers fall into single-mode and multi-mode fibers. Single-mode optical modules use single-mode fibers, and multi-mode optical modules use multi-mode fibers. For a non-BIDI optical module, each optical interface must be configured with a Tx optical fiber and an Rx optical fiber of the same type. For a BIDI optical module, only one optical fiber needs to be configured.

NOTE

The fibers and optical modules supported by Huawei switches are being updated. For the latest information, visit <http://support.huawei.com/enterprise/en/doc/EDOC1000013597?section=j07w&topicName=pluggable-modules-for-interfaces> or contact your local Huawei sales office.

Stack Cables

The S5720-EI series switches support service port stacking and stack card stacking. The applicable stack cables are as follows:

- AOC cable

An active optical network (AOC) cable integrates an optical module and a fiber. The AOC cables are available in SFP-10G-AOC3M and SFP-10G-AOC10M.

- SFP+ high-speed cable

The SFP+ high-speed cable also integrates an optical module and a fiber. The SFP+ high-speed cables are available in SFP-10G-CU1M, SFP-10G-CU3M, SFP-10G-CU5M, and SFP-10G-CU10M.

- Stack card

The stack card provides two QSFP+ optical ports for stack connection, and can be installed in the rear card slot of the S5720-C-EI and S5720-PC-EI series chassis.

The following table lists the stack cable types and connectors.

Stack cable types and connectors applicable to the S5720-EI series

Stack Cable	Model	Cable Length	Connector
AOC	SFP-10G-AOC3M	3 m	SFP+
	SFP-10G-AOC10M	5 m	SFP+
SFP+ high-speed	SFP-10G-CU1M	1 m	SFP+
	SFP-10G-CU3M	3 m	SFP+
	SFP-10G-CU5M	5 m	SFP+
	SFP-10G-CU10M	10 m	SFP+

 **NOTE**

For more information about stack cables applicable to the S5720-EI series, visit <http://support.huawei.com/enterprise/en/doc/EDOC1000013597?section=j07f&topicName=cables> or contact your local Huawei sales office.

Safety and Regulatory Compliance

The following table lists the safety and regulatory compliance of the S5720-EI.

Safety and regulatory compliance of the S5720-EI series

Certification Category	Description
Safety	<ul style="list-style-type: none"> IEC 60950-1 EN 60950-1/A11/A12 UL 60950-1 CSA C22.2 No 60950-1 AS/NZS 60950.1 CNS 14336-1 IEC60825-1 IEC60825-2 EN60825-1 EN60825-2
Electromagnetic Compatibility (EMC)	<ul style="list-style-type: none"> CISPR22 Class A CISPR24 EN55022 Class A EN55024 ETSI EN 300 386 Class A CFR 47 FCC Part 15 Class A ICES 003 Class A AS/NZS CISPR22 Class A VCCI Class A IEC61000-4-2

Certification Category	Description
	<ul style="list-style-type: none"> • ITU-T K 20 • ITU-T K 21 • ITU-T K 44 • CNS13438
Environment	<ul style="list-style-type: none"> • RoHS • REACH • WEEE

 **NOTE**

- EMC: electromagnetic compatibility
- CISPR: International Special Committee on Radio Interference
- EN: European Standard
- ETSI: European Telecommunications Standards Institute
- CFR: Code of Federal Regulations
- FCC: Federal Communication Commission
- IEC: International Electrotechnical Commission
- AS/NZS: Australian/New Zealand Standard
- VCCI: Voluntary Control Council for Interference
- UL: Underwriters Laboratories
- CSA: Canadian Standards Association
- IEEE: Institute of Electrical and Electronics Engineers
- RoHS: restriction of the use of certain hazardous substances
- REACH: Registration Evaluation Authorization and Restriction of Chemicals
- WEEE: Waste Electrical and Electronic Equipment

MIB and Standards Compliance

Supported MIBs

The following table lists the MIBs supported by the S5720-EI.

MIBs supported by the S5720-EI series

Category	MIB
Public MIB	<ul style="list-style-type: none"> • BRIDGE-MIB • DISMAN-NSLOOKUP-MIB • DISMAN-PING-MIB • DISMAN-TRACEROUTE-MIB • ENTITY-MIB • EtherLike-MIB • IF-MIB • IP-FORWARD-MIB • IPv6-MIB • LAG-MIB • LLDP-EXT-DOT1-MIB • LLDP-EXT-DOT3-MIB • LLDP-MIB

Category	MIB
	<ul style="list-style-type: none"> • MPLS-FTN-STD-MIB • MPLS-L3VPN-STD-MIB • MPLS-LDP-GENERIC-STD-MIB • MPLS-LDP-STD-MIB • MPLS-LSR-STD-MIB • MPLS-TE-STD-MIB • NOTIFICATION-LOG-MIB • NQA-MIB • OSPF-TRAP-MIB • P-BRIDGE-MIB • Q-BRIDGE-MIB • RFC1213-MIB • RIPv2-MIB • RMON2-MIB • RMON-MIB • SAVI-MIB • SNMP-FRAMEWORK-MIB • SNMP-MPD-MIB • SNMP-NOTIFICATION-MIB • SNMP-TARGET-MIB • SNMP-USER-BASED-SM-MIB • SNMPv2-MIB • TCP-MIB • UDP-MIB
Huawei-proprietary MIB	<ul style="list-style-type: none"> • HUAWEI-AAA-MIB • HUAWEI-ACL-MIB • HUAWEI-ALARM-MIB • HUAWEI-ALARM-RELIABILITY-MIB • HUAWEI-BASE-TRAP-MIB • HUAWEI-BRAS-RADIUS-MIB • HUAWEI-BRAS-SRVCFG-EAP-MIB • HUAWEI-BRAS-SRVCFG-STATICUSER-MIB • HUAWEI-CBQOS-MIB • HUAWEI-CDP-COMPLIANCE-MIB • HUAWEI-CONFIG-MAN-MIB • HUAWEI-CPU-MIB • HUAWEI-DAD-TRAP-MIB • HUAWEI-DC-MIB • HUAWEI-DATASYNC-MIB • HUAWEI-DEVICE-MIB • HUAWEI-DHCPR-MIB • HUAWEI-DHCPS-MIB • HUAWEI-DHCP-SNOOPING-MIB • HUAWEI-DIE-MIB

Category	MIB
	<ul style="list-style-type: none"> • HUAWEI-DNS-MIB • HUAWEI-DLDP-MIB • HUAWEI-ELMI-MIB • HUAWEI-ERPS-MIB • HUAWEI-ERRORDOWN-MIB • HUAWEI-ENERGYMNGT-MIB • HUAWEI-EASY-OPERATION-MIB • HUAWEI-ENTITY-EXTENT-MIB • HUAWEI-ENTITY-TRAP-MIB • HUAWEI-ETHARP-MIB • HUAWEI-ETHOAM-MIB • HUAWEI-FLASH-MAN-MIB • HUAWEI-FWD-RES-TRAP-MIB • HUAWEI-GARP-APP-MIB • HUAWEI-GTSM-MIB • HUAWEI-HGMP-MIB • HUAWEI-HWTACACS-MIB • HUAWEI-IF-EXT-MIB • HUAWEI-INFOCENTER-MIB • HUAWEI-IPPOOL-MIB • HUAWEI-IPV6-MIB • HUAWEI-ISOLATE-MIB • HUAWEI-L2IF-MIB • HUAWEI-L2MAM-MIB • HUAWEI-L2VLAN-MIB • HUAWEI_LDT-MIB • HUAWEI-LLDP-MIB • HUAWEI-MAC-AUTHEN-MIB • HUAWEI-MEMORY-MIB • HUAWEI-MFF-MIB • HUAWEI-MFLP-MIB • HUAWEI-MSTP-MIB • HUAWEI-MULTICAST-MIB • HUAWEI-NAP-MIB • HUAWEI-NTPV3-MIB • HUAWEI-PERFORMANCE-MIB • HUAWEI-PORT-MIB • HUAWEI-PORTAL-MIB • HUAWEI-QINQ-MIB • HUAWEI-RIPv2-EXT-MIB • HUAWEI-RM-EXT-MIB • HUAWEI-RRPP-MIB • HUAWEI-SECURITY-MIB • HUAWEI-SEP-MIB • HUAWEI-SNMP-EXT-MIB

Category	MIB
	<ul style="list-style-type: none"> • HUAWEI-SSH-MIB • HUAWEI-STACK-MIB • HUAWEI-SWITCH-L2MAM-EXT-MIB • HUAWEI-SWITCH-SRV-TRAP-MIB • HUAWEI-SYS-MAN-MIB • HUAWEI-TCP-MIB • HUAWEI-TFTPC-MIB • HUAWEI-TRNG-MIB • HUAWEI-XQOS-MIB

 **NOTE**

For more information about MIBs supported by the S5720-EI series, visit <https://support.huawei.com/enterprise/en/switches/s5700-pid-6691579?category=reference-guides&subcategory=mib-reference>.

Standard Compliance

The following table lists the standards that the S5720-EI complies with.

Standard compliance list of the S5720-EI series

Standard Organization	Standard or Protocol
IETF	<ul style="list-style-type: none"> • RFC 768 User Datagram Protocol (UDP) • RFC 792 Internet Control Message Protocol (ICMP) • RFC 793 Transmission Control Protocol (TCP) • RFC 826 Ethernet Address Resolution Protocol (ARP) • RFC 854 Telnet Protocol Specification • RFC 951 Bootstrap Protocol (BOOTP) • RFC 959 File Transfer Protocol (FTP) • RFC 1058 Routing Information Protocol (RIP) • RFC 1112 Host extensions for IP multicasting • RFC 1157 A Simple Network Management Protocol (SNMP) • RFC 1256 ICMP Router Discovery • RFC 1305 Network Time Protocol Version 3 (NTP) • RFC 1349 Internet Protocol (IP) • RFC 1493 Definitions of Managed Objects for Bridges • RFC 1542 Clarifications and Extensions for the Bootstrap Protocol • RFC 1643 Ethernet Interface MIB • RFC 1757 Remote Network Monitoring (RMON) • RFC 1901 Introduction to Community-based SNMPv2 • RFC 1902-1907 SNMP v2 • RFC 1981 Path MTU Discovery for IP version 6 • RFC 2131 Dynamic Host Configuration Protocol (DHCP) • RFC 2328 OSPF Version 2 • RFC 2453 RIP Version 2 • RFC 2460 Internet Protocol, Version 6 Specification (IPv6) • RFC 2461 Neighbor Discovery for IP Version 6 (IPv6) • RFC 2462 IPv6 Stateless Address Auto configuration • RFC 2463 Internet Control Message Protocol for IPv6 (ICMPv6)

Standard Organization	Standard or Protocol
	<ul style="list-style-type: none"> • RFC 2474 Differentiated Services Field (DS Field) • RFC 2740 OSPF for IPv6 (OSPFv3) • RFC 2863 The Interfaces Group MIB • RFC 2597 Assured Forwarding PHB Group • RFC 2598 An Expedited Forwarding PHB • RFC 2571 SNMP Management Frameworks • RFC 2865 Remote Authentication Dial In User Service (RADIUS) • RFC 3046 DHCP Option82 • RFC 3376 Internet Group Management Protocol, Version 3 (IGMPv3) • RFC 3513 IP Version 6 Addressing Architecture • RFC 3579 RADIUS Support For EAP • RFC 4271 A Border Gateway Protocol 4 (BGP-4) • RFC 4760 Multiprotocol Extensions for BGP-4 • draft-grant-tacacs-02 TACACS+ • RFC 6241 Network Configuration Protocol (NETCONF) • RFC 6020 YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)
IEEE	<ul style="list-style-type: none"> • IEEE 802.1D Media Access Control (MAC) Bridges • IEEE 802.1p Traffic Class Expediting and Dynamic Multicast Filtering • IEEE 802.1Q Virtual Bridged Local Area Networks • IEEE 802.1ad Provider Bridges • IEEE 802.2 Logical Link Control • IEEE Std 802.3 CSMA/CD • IEEE Std 802.3ab 1000BASE-T specification • IEEE Std 802.3ad Aggregation of Multiple Link Segments • IEEE Std 802.3ae 10GE WEN/LAN Standard • IEEE Std 802.3x Full Duplex and flow control • IEEE Std 802.3z Gigabit Ethernet Standard • IEEE802.1ax/IEEE802.3ad Link Aggregation • IEEE 802.3ah Ethernet in the First Mile • IEEE 802.1ag Connectivity Fault Management • IEEE 802.1ab Link Layer Discovery Protocol • IEEE 802.1D Spanning Tree Protocol • IEEE 802.1w Rapid Spanning Tree Protocol • IEEE 802.1s Multiple Spanning Tree Protocol • IEEE 802.1x Port based network access control protocol • IEEE 802.3af DTE Power via MIDI • IEEE 802.3at DTE Power via the MDI Enhancements
ITU	<ul style="list-style-type: none"> • ITU SG13 Y.17ethoam • ITU SG13 QoS control Ethernet-Based IP Access • ITU-T Y.1731 ETH OAM performance monitor
ISO	<ul style="list-style-type: none"> • ISO 10589 IS-IS Routing Protocol
MEF	<ul style="list-style-type: none"> • MEF 2 Requirements and Framework for Ethernet Service Protection • MEF 9 Abstract Test Suite for Ethernet Services at the UNI

Standard Organization	Standard or Protocol
	<ul style="list-style-type: none"> • MEF 10.2 Ethernet Services Attributes Phase 2 • MEF 11 UNI Requirements and Framework • MEF 13 UNI Type 1 Implementation Agreement • MEF 15 Requirements for Management of Metro Ethernet Phase 1 Network Elements • MEF 17 Service OAM Framework and Requirements • MEF 20 UNI Type 2 Implementation Agreement • MEF 23 Class of Service Phase 1 Implementation Agreement • Xmodem XMODEM/YMODEM Protocol Reference

NOTE

The listed standards and protocols are fully or partially supported by Huawei switches. For details, visit <http://e.huawei.com> or contact your local Huawei sales office.

Ordering Information

Ordering information of the S5720-EI series

Item	Product Description
1	S5720-32P-EI-AC (24 Ethernet 10/100/1000 ports, 8 Gig SFP, AC 110/220 V, front access)
2	S5720-32X-EI-AC (24 Ethernet 10/100/1000 ports, 4 Gig SFP, 4 10 Gig SFP+, AC 110/220 V, front access)
3	S5720-32X-EI-24S-AC (24 Gig SFP, 4 Ethernet 10/100/1000 ports, 4 10 Gig SFP+, AC 110/220 V, front access)
4	S5720-32X-EI-24S-DC (24 Gig SFP, 4 Ethernet 10/100/1000 ports, 4 10 Gig SFP+, DC, front access)
5	S5720-36C-EI-AC (28 Ethernet 10/100/1000 ports, 4 of which are dual-purpose 10/100/1000 or SFP, 4 10 Gig SFP+, 1 interface slot, with 150 W AC)
6	S5720-36C-PWR-EI-AC (28 Ethernet 10/100/1000 PoE+ ports, 4 of which are dual-purpose 10/100/1000 or SFP, 4 10 Gig SFP+, with 500 W AC power)
7	S5720-36PC-EI-AC (28 Ethernet 10/100/1000 ports, 4 of which are dual-purpose 10/100/1000 or SFP, 4 Gig SFP, 1 interface slot, with 150 W AC)
8	S5720-36C-EI-28S-AC (28 Gig SFP, 4 of which are dual-purpose 10/100/1000 or SFP, 4 10 Gig SFP+, with 1 interface slot, with 150 W AC power supply)
9	S5720-36C-EI-28S-DC (28 Gig SFP, 4 of which are dual-purpose 10/100/1000 or SFP, 4 10 Gig SFP+, with 1 interface slot, with 150 W DC power supply)
10	S5720-50X-EI-AC (46 Ethernet 10/100/1000 ports, 4 10 Gig SFP+, AC 110/220 V, front access)
11	S5720-50X-EI-DC (46 Ethernet 10/100/1000 ports, 4 10 Gig SFP+, DC, front access)
12	S5720-50X-EI-46S-AC (46 Gig SFP, 4 10 Gig SFP+, AC 110/220 V, front access)
13	S5720-50X-EI-46S-DC (46 Gig SFP, 4 10 Gig SFP+, DC, front access)
14	S5720-52X-EI-AC (48 Ethernet 10/100/1000 ports, 4 10 Gig SFP+, AC 110/220 V)
15	S5720-52P-EI-AC (48 Ethernet 10/100/1000 ports, 4 Gig SFP, AC 110/220 V)
16	S5720-56C-EI-48S-AC (48 Gig SFP, 4 10 Gig SFP+, with 1 interface slot, with 150 W AC power supply)
17	S5720-56C-EI-48S-DC (48 Gig SFP, 4 10 Gig SFP+, with 1 interface slot, with 150 W DC power supply)
18	S5720-56C-EI-AC (48 Ethernet 10/100/1000 ports, 4 10 Gig SFP+, with 1 interface slot, with 150 W AC power supply)

Item	Product Description
19	S5720-56C-EI-DC (48 Ethernet 10/100/1000 ports, 4 10 Gig SFP+, with 1 interface slot, with 150 W DC power supply)
20	S5720-56PC-EI-AC (48 Ethernet 10/100/1000 ports, 4 Gig SFP, with 1 interface slot, with 150 W AC power supply)
21	S5720-56C-PWR-EI-AC (48 Ethernet 10/100/1000 PoE+ ports, 4 10 Gig SFP+, with 1 interface slot, with 500 W AC power supply)
22	S5720-56C-PWR-EI-DC (48 Ethernet 10/100/1000 PoE+ ports, 4 10 Gig SFP+, with 1 interface slot, with 650 W DC power supply)
23	S5720-56C-PWR-EI-AC1 (48 Ethernet 10/100/1000 PoE+ ports, 4 10 Gig SFP+, with 1 interface slot, with 1150 W AC power supply)
24	2 10 Gig SFP+ Interface Card (used in S5720EI series)
25	Dedicated stack card with 2*QSFP+ interface (Including one PCS of 1M QSFP+ cable, Used in S5720EI series)
26	RPS1800 redundant power supply
27	S5720-EI Fan box (F, FAN panel side intake)
28	150 W AC Power Module
29	150 W DC Power Module
30	500 W AC PoE Power Module
31	650 W DC PoE Power Module
32	1150 W AC PoE Power Module
33	1000 W AC PoE Power Module

More Information


For more information about Huawei Campus Switches, visit <http://e.huawei.com> or contact us in the following ways:

- Global service hotline: <http://e.huawei.com/en/service-hotline>
- Logging in to the Huawei Enterprise technical support website: <http://support.huawei.com/enterprise/>
- Sending an email to the customer service mailbox: support_e@huawei.com

Copyright © Huawei Technologies Co., Ltd. 2019. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions

 HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Huawei Technologies Co., Ltd.

Address: Huawei Industrial Base Bantian,
Longgang Shenzhen 518129 People's
Republic of China

Website: e.huawei.com